

Elakeview Enterprise LTD



LED Flood Light 100W AC277-480V 4000K

Product description: LED Flood Light 100W AC277-480V 4000K

Model Name: FL100WH4K

Order SKU: 700013HRC-4K



◇ Features

- Energy savings up to 70% vs 250W MH
- Sealed die-casting profile for outdoor applications
- High quality of heat-resisting polycarbonate optical lens
- Excellent Wind Resistance
- Preinstalled receptacle for twist-lock photocell
- Preinstalled U bracket/Trunnion mount. Mount options available:



Slipfitter:



Adjustable Horizontal Arm:

◇ Specifications

Rated Voltage (V)	AC277-480V
Rated Wattage (W)	100W
Frequency (Hz)	50/60 Hz
Rated Input Current (mA)	700mA
Power Factor	>0.90
Luminous Flux (LM)	13,266 LM
Color Temperature	Cool Light 4000K
Color Rendering Index (Ra)	>80
Beam Angle	T3
Lamp Efficacy (LM/W)	132.91
Rated Lamp Lifetime (h)	100,000
Dimming	0-10V Dimming
Dimension (mm)	336*590*80
IP Rating	65
Operating Temperature	-40 to 55 degC
Material	Aluminum + PC Lens
Certificate	cULus, DLC, FCC, Hg, IP65, Rohs



