

LED VAPOR PROOF HIGH BAY STRIP



MODEL: VP8FTUCCTW

SKU: 900015UCCTW8FTA

LED VAPOR PROOF HIGH BAY STRIP

ELAKEVIEW ENTERPRISE LTD.

PRODUCT DESCRIPTION


The Elakeview LED Vapor Proof High Bay strip is designed for environments where weather and/or dust resistant lighting application is required. Works perfectly for all commercial and industrial applications



HIGHLIGHTS



- AC120-347V
- Class2 0-10V Dimming Driver, 4/6KV surge protector, w/overtemperature protection
- Wattage Selectable: 65/75/90W
- Color Temperature Selectable : 3500/4000/5000K
- Efficacy: 132LM/W
- Receptacle for Microwave Dimming Sensor (Sensor Sold Separately)
- Suitable for Damp Location
- Easy to Install and Operate
- Over 50,000 Hours Life Time
- DLC 5.1, cUL Listed
- Standard 5 Years Warranty



APPLICATIONS

Suitable to storage areas, farms, underground parking, food industry, painting industry, etc.

ORDERING INFORMATION

ORDER SKU	DLC MODEL#	DLC PRODUCT ID	CRI	INPUT VOLTAGE	POWER	EFFICACY	DELIVERED LUMENS	CCT	FINISH	SIZE
900015UCCTW8FTA	VP8FTUCCTW	S-680N2L	>80	AC120-347V	65/75/90W	132LM/W	8580/9900/11880LM	3500/4000/5000K	WHITE	8FT
900015UCCTW2FT	VP2FTUCCTW	S-ECM09R	>80	AC120-347V	15/20/25W	130LM/W	2750/3300/4400LM	3500/4000/5000K	WHITE	2FT
900015UCCTW4FTA	VP4FTUCCTW	S-7KML5V	>80	AC120-347V	34/38/45W	132LM/W	4488/5016/5940LM	3500/4000/5000K	WHITE	4FT
900015UCCTW4FT2	VP4FTUCCTW2	S-4BMS88	>80	AC120-347V	26/35/45W	142LM/W	3640/4900/6300LM	3500/4000/5000K	WHITE	4FT

PRODUCT SPECIFICATIONS

POWER TUNABLE	SYSTEM EFFICACY	LUMENS	CCT (K) TUNABLE	CRI	VOLTAGE	POWER FREQ	DIMENSIONS (MM)	POWER FACTOR
65/75/90W	132LMW	8580/9900/11880LM	3500/4000/5000K	>80	120-347V	50/60HZ	2400*96.8*78.8	>0.9

DIMENSIONS

