

M



**Intended Use**

Surface or stem-mounted lensed fixture for general illumination in commercial offices and indoor retail applications.

**Construction**

Die-formed, cold-rolled steel housing finished with baked white enamel.

Standard door is fully gasketed flush steel with sturdy tee hinges and opposing, rotary-action cam latches.

Spring-loaded latches optional.

Aluminum doors available, flush or regressed with choice of finish.

For surface or stem mounting, unit or row installation.

For unit mounting on stems: Minimum of two mounting stems required on 1'x4' models. Four stems required on 2'x4' models and 4'x4' models.

For row mounting on stems: Use half the number of stems required for unit mounting except on last fixture in row.

Example: on 2'x4' two-lamp and four-lamp fixtures, use two stems per fixture plus two per row.

**Electrical**

Ballast disconnect provided standard where required to comply with U.S. and Canadian electrical codes.

**Listings**

UL Listed. CUL Listed or CSA Certified to Canadian Standards. NOM Certified – optional.

**ORDERING INFORMATION**

For shortest lead times, configure products using **bolded options**.

**Example: 2M 2 32 RW A19 MVOLT GEB10IS**

Series	Number of lamps <sup>3</sup>	Lamp type <sup>3</sup>	Door	Diffuser	Voltage
<b>M</b> 1' wide	1	<b>17</b> 17W T8 (24")	<b>(blank)</b> Flush steel, white	<b>A12</b> #12 pattern acrylic	<b>MVOLT</b>
<b>2M</b> 2' wide	2	32 32W T8 (48")	FN Flush aluminum, natural	<b>A12125</b> #12 pattern acrylic, .125" thick	347 <sup>6</sup>
<b>4M</b> 4' wide <sup>4</sup>	3 <sup>1</sup>	CF40 40W TTS (24")	FM Flush aluminum, matte black	<b>A19</b> #19 pattern acrylic, .156" thick	
	4	<b>U31</b> 31W T8 U (1-5/8" leg)	<b>FW</b> Flush aluminum, white	PC1S Parabolic plastic cube louver, specular silver	
	6	U316 31W T8 U (6" leg) <sup>2</sup>	RN Regressed aluminum, natural		
	8		RM Regressed aluminum, matte black		
	Not included.		<b>RW</b> Regressed aluminum, white		




Ballast configuration	Ballast	Lamp color	Options
(blank) 1- and/or 2-lamp ballasts per Lithonia Lighting standards	<b>GEB10IS</b> T8 and CF electronic ballast, ≤10% THD, instant start	<b>LP735</b> Lamped with 700 series, 3500° K	<b>EL</b> Emergency battery pack <sup>5</sup>
<b>1/3</b> One 3-lamp ballast	<b>GEB10RS</b> T8 and CF electronic ballast, ≤10% THD, programmed rapid start		CSA Meets Canadian standards
<b>1/4</b> One 4-lamp ballast			NOM Meets Mexican standards

**ADDITIONAL INFORMATION**

For additional product information, visit [www.lithonia.com](http://www.lithonia.com).

CONFIGURATIONS						
NOMINAL SIZE	SERIES	NUMBER OF LAMPS	LAMP TYPE	LENGTH IN.(CM)	WIDTH IN.(CM)	HEIGHT IN.(CM)
1'x4'	M	1, 2, 3	32	48 (121.9)	12 (30.5)	3-3/4 (9.5)
2'x2'	2M	1, 2	U316	24 (61.0)	24 (61.0)	3-3/4 (9.5)
2'x2'	2M	2, 3	17, U31, CF40	24 (61.0)	24 (61.0)	3-3/4 (9.5)
2'x2'	2M	4	17, CF40	24 (61.0)	24 (61.0)	3-3/4 (9.5)
2'x4'	2M	2, 3, 4	32	48 (121.9)	24 (61.0)	3-3/4 (9.5)
4'x4'	4M	4, 6, 8	32	48 (121.9)	48 (121.9)	3-3/4 (9.5)

Drawings are for dimensional detail only and may not represent actual mechanical configuration. Dimensions are shown in inches (centimeters) unless otherwise noted.



**Notes**

- 1 Stem mounting not available on 3-lamp 2x4 models.
- 2 Not available on 3-lamp models. Use U31.
- 3 See Configurations table for lamp compatibility.
- 4 Center mullion standard on 4M.
- 5 Consult [www.lithonia.com](http://www.lithonia.com) for available options.
- 6 Available only with CSA option.