

FEATURES & SPECIFICATIONS

INTENDED USE

Provides maintenance-free, energy-efficient accent and/or task lighting in residential and light commercial applications. Mix and match fitters with any number of decorative shades/diffusers from Lithonia Lighting (see decorative shade ordering information on second page) to create a look that perfectly compliments any décor. Ideal for mounting over kitchen islands, countertops, bars, desks and tables.

CONSTRUCTION

Cast aluminum fitters and matching canopies are finished in either a bronze or polished brushed nickel. Includes three set screws which hold decorative shades that mount to the inside of the fitter. These shades have a standard 2-1/4" neck.

Decorative shades that mount to the outside of the fitter include decorative finials or decorative rods, three bronze and three polished brushed nickel, that screw into the fitter.

Decorative shades are available in hand-blown glass, prismatic glass or metal. All decorative shades fit both fitter styles.

Decorative shades sold separately (see shade ordering information on second page).

OPTICS

Each fitter contains three 3000K high-performance LEDs which maintain 274 lumen output at 50,000-hour life.

ELECTRICAL

LED driver is 120V and operates at 60Hz.

Fully dimmable down to 10%. Works with most standard incandescent dimmers. See chart on second page for suggested dimmers.

INSTALLATION

Suspended mount from ceiling. Includes 78" of cable for tool-free mounting height adjustment. Excess cable fits within canopy - no cutting necessary.

All mounting hardware included.

LISTINGS

UL listed to U.S. and Canadian safety standards.

WARRANTY

5-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

NOTE: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25°C.

Specifications subject to change without notice.

Catalog Number
Notes
Type

LED Mini-Pendant Fitters with Mix-and-Match Shades

MDP

HIGH-PERFORMANCE LED



Bullet Fitter



Cylinder Fitter



See reverse side for decorative shade ordering information.

Dimensions

Bullet Fitter:

Canopy Width: 5" (12.7)
Canopy Height: 1-7/8" (4.8)
Fitter Width: 2-3/4" (7)
Fitter Height: 2" (5.1)

Cylinder Fitter:

Canopy Width: 4-1/2" (11.4)
Canopy Height: 1-7/8" (4.8)
Fitter Width: 2-5/8" (6.7)
Fitter Height: 1-7/8" (4.8)

Both fitter styles include 78" of cable for tool-free mounting height adjustment. All dimensions are inches (centimeters).

ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Example: MDPB BZ

Series ¹	Finish
MDPB Bullet LED mini-pendant fitter	BZ Bronze
MDPC Cylinder LED mini-pendant fitter	BNP² Polished Brushed Nickel

SHADE ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Example: DTCL 1005

Model (see product images on back of sheet)			
DRBL 1001	Ball shade in opal white finish	DCBL 1009	Concave bell shade in amber twist finish
DRBL 1008	Ball shade in green melon finish	DGDT 1003	Cylinder dot shade in frosted white finish
DBEL 1001	Bell shade in opal white finish	DGWV 1003	Cylinder wave shade in frosted white finish
DBLT 1004	Bullet shade in caramel swirl finish	DGNG 1007	Glass in glass shade in blue finish
DCNE 1001	Cone shade in opal white finish	DSCL 1001	Short cylinder shade in opal white finish
DCNE 1002	Cone shade in white melon finish	DSCL 1005	Short cylinder shade in apple red finish
DCNE 1008	Cone shade in green melon finish	DSCL 1009	Short cylinder shade in amber twist finish
DMCN BZ	Metal cone shade in bronze finish	DSCL 1010	Short cylinder shade in white drizzle finish
DMCN BNP	Metal cone shade in polished brushed nickel finish		


Notes

- Glass shades must be ordered separately. See Shade Ordering Information.
- BNP is only available with MDPC.

LED Mini-Pendant Fitters and Shades

PHOTOMETRICS

Full photometric data report available within two weeks from request. Consult factory. Actual wattage may differ by +/- 5% when operating at 120V +/- 10%. Actual performance may differ as a result of end-user environment and application.



Suggested Dimmers

The MDP Series is designed to operate with most standard Triac Based (Forward Phase-Control or Leading Edge) dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested with the MDP Series and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.

Manufacturer	Series	Part Number(s)
Leviton	Illumitech	IPI06-XXX
Leviton	Trimatron	6602-1, 6681-X, 6683-X, 6684-X, 700-X, 705-X
Leviton	SureSlide	6631
Leviton	True Touch	6606-1LM
Lutron	Skylark	S-600, S2-LH
Lutron	Nova T	NTELV-600
Lutron	Faetra	FAELV-500-XX
Lutron	Acenti	ACE06-XXX
Lutron	Vizia	VZE04

Note: When the installation exceeds 10 fixtures on a single dimmer or distribution lengths exceed 100 feet, please confirm that the end product performs properly. This is caused by a high degree of variability in the triac dimmers.

SHADES

Shades/diffusers must be ordered separately from fitters. More options may be available (consult factory).

All decorative shades are hand-blown glass (variations in pattern may exist) unless otherwise specified. Shades using decorative rods/finals include rods/finals in both bronze and polished brushed nickel.

