

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: CLX L48 5000LM SEF WDL MVOLT GZ10 40K 80CRI WH

Series	Length	Nominal lumens	Performance package	Louver	Lens
CLX LED linear	L24 24" ^{1,2}	1500LM 1,500 lumens	SEF Standard efficiency ⁵ HEF Premium efficiency	(Blank) Less louver SBLW Straight blade louver, white ⁶ SBLMB Straight blade louver, matte black ⁶ SBLGV Straight blade louver, galvanized ⁶ SBLSKGY Straight blade louver, smoke gray ⁶	L/Lens Less lens FDL Flat diffuse ^{7,8} RDL Round diffuse ^{7,8} WDL Wide diffuse ^{7,8}
		2000LM 2,000 lumens			
		2500LM 2,500 lumens			
		3500LM 3,500 lumens			
		4500LM 4,500 lumens			
		5000LM 5,000 lumens ^{3,4}			
	L36 36" ²	2250LM 2,250 lumens			
		3000LM 3,000 lumens			
		3750LM 3,750 lumens			
		5250LM 5,250 lumens			
		6750LM 6,750 lumens			
		7500LM 7,500 lumens ^{3,4}			
	L48 48"	3000LM 3,000 lumens			
		4000LM 4,000 lumens			
		5000LM 5,000 lumens			
		7000LM 7,000 lumens ²			
		9000LM 9,000 lumens ²			
		10000LM 10,000 lumens ^{2,4}			
	L96 96"	6000LM 6,000 lumens			
		8000LM 8,000 lumens			
		10000LM 10,000 lumens			
		14000LM 14,000 lumens ^{2,4}			
		18000LM 18,000 lumens ^{2,4}			
		20000LM 20,000 lumens ^{2,4}			

Distribution	Voltage	Driver ¹⁴	Color temperature	Coloring rendering index
(Blank) General	MVOLT 120-277V ¹⁰	277 277V	30K 3000 K	80CRI 80 CRI
ND Narrow ^{8,9}	120 120V	347 347V ^{12,13}	35K 3500 K	90CRI 90 CRI
WD Wide ^{8,9}	208 208V ¹¹	480 480V ^{12,13}	40K 4000 K	
AD2 Aisle, 24° off center ^{8,9}	240 240V ¹¹		50K 5000 K	

Options	Finish
PS1050 Emergency battery pack, 10W, CA Title 20 Noncompliant ^{2,11,13,16,17} E10WLCP Emergency battery pack, 10W Linear Constant Power, Certified in CA Title 20 MAEDBS ^{12,11,13,16,17} BGTD Generator transfer device, not available with PS1050 ^{13,16,18} OCS 5', 18/3 Reloc selectable One Pass cable ¹⁶ HA High ambient, for use in ambient temperatures up to 50°C ¹¹ EPNKO Decorative endplate, no knock out ¹⁹ OUTCTR Wiring leads pulled through back center of fixture ²¹ OUTEND Wiring leads pulled through end of fixture ²¹ Cord Sets: CS1W Straight blade plug, 120V ^{10,16} CS3W NEMA twist-lock plug, 120V ^{10,16} CS7W Straight blade plug, 277V ^{10,16} CS11W NEMA twist-lock plug, 277V ^{10,16} CS25W NEMA twist-lock plug, 347V ^{10,16} CS97W NEMA twist-lock plug, 480V ^{10,16} CS93W 600V SEOWW white cord, no plug (no voltage required) CS6WG16STOWD5D 6' white cord, 16/5, no plug, includes low voltage dimming wires (no voltage required) ¹⁵	WH White GALVW Galvanized with white lens end caps GALVB Galvanized with black lens end caps MB Matte black SKGYW Smoke gray with white lens end caps SKGYB Smoke gray with black lens end caps
PLR Plug-in wiring, see page 16 for ordering information PLR1LVG Plug-in wiring, low voltage dimming ²² RRL RELOC-ready luminaire. See page 15 for ordering information SPD Surge protection device, provides up to 6kV protection ²⁰ BAA Buy America(n) Act Compliant nLight® Wireless: ^{23,24} NLTAIR2 RES7 nLight® Generation 2 enabled PIR integral occupancy sensor with automatic dimming photocell NLTAIR2 RES7PDT nLight AIR Generation 2 enabled dual technology integral occupancy sensor with automatic dimming photocell NLTAIR2 RIO No sensor control	nLight® Wired: ^{23,25} N100 nLight® without lumen management NES7 nLight® nES 7 PIR integral occupancy sensor ²⁶ NESPDT7 nLight® nES PDT 7 dual technology integral occupancy control ²⁶ NES7ADCX nLight® nES 7 ADCX PIR integral occupancy sensor with automatic dimming photocell ²⁶ NESPDT7ADCX nLight® nES PDT 7 dual technology integral occupancy sensor with automatic dimming photocell ²⁶ Individual controls: ^{23,25} MSD7 PIR integral occupancy sensor MSDPDT7 PDT 7 dual technology integral occupancy control MSD7ADC PIR integral occupancy sensor with automatic dimming control photocell MSDPDT7ADC PDT integral occupancy sensor with automatic dimming control photocell

See Accessories and footnotes on next page

Accessories: Order as separate catalog number.			
Mounting:		THCLX ____	Tong hanger (Must specify color) (one pair) ²⁸
ZACVH M100	Adjustable 10' aircraft cable with Y hanger (1 pair)	CLXANGBKT ____	Angle bracket, (Must specify color) (one pair) ²⁸
ZAC120	One adjustable aircraft cable with canopy 120" ²⁷	HC36 M12	Hanger chain, 36" (1 pair)
		Sensors & Controls:	
ZACFP120	One adjustable aircraft cable with feed (3 conductor) and canopy, 120" ²⁷	LSXR	Sensor Switch ® LSXR occupancy sensor ²⁹
ZACFPD120	One adjustable aircraft cable with feed (5 conductor) and canopy 120" ²⁷	NPP16D	nLight® switching/dimming module
ZAC240	One adjustable aircraft cable with canopy 240" ²⁷	NPP16DER	nLight® switching/dimming module with emergency relay
ZACFP240	One adjustable aircraft cable with feed (3 conductor) and canopy, 240" ²⁷	rPP20D	nLight® air dimming/switching module
ZACFPD240	One adjustable aircraft cable with feed (5 conductor) and canopy 240" ²⁷	Reflectors:	
SQ_	Swivel stem hanger (specify length in 2" increments up to 48") ²⁷	CLXRW24_	Wide decorative 24" reflector, (Must specify color) ³⁰
		CLXRW36_	Wide decorative 36" reflector, (Must specify color) ³⁰
		CLXRW48_	Wide decorative 48" reflector, (Must specify color) ³⁰
		CLXRW96_	Two wide decorative 48" reflectors, (Must specify color) ³⁰
		CLXRN24	Narrow 24" reflector, (Must specify color) ³¹
		CLXRN36	Narrow 36" reflector, (Must specify color) ³¹
		CLXRN48	Narrow 48" reflector, (Must specify color) ³¹
		CLXRN96	Two narrow 48" reflectors, (Must specify color) ³¹
		Wireguards:	
		WGCLX24_	24" wireguard, (Must specify color) ³²
		WGCLX36_	36" wireguard, (Must specify color) ³²
		WGCLX48_	48" wireguard, XX, (Must specify color) 96" fixture requires two ³²

Notes

- Not available with OUTCTR option.
- Not available with HA option.
- Not available with SEF when ordered in combination with EZ1.
- Not available with NLTAIR2 RES7, NLTAIR2 RES7PDT, or NLTAIR2 RIO.
- Not available with EZ1 when ordered with L24 with 5000LM or L36 with 7500LM.
- When ordered with L24 only available with 1500LM or 2000LM in combination with GZ10 driver. Not for use with THCLX, CLXANGBKT, CLX reflectors or WGCLX accessories. Not available with RDL lens options.
- Only available with general distribution.
- Not available with CLXRN accessories.
- Available L/LENS only.
- Not available with PS1050, E10WLCP, or BGTD.
- Not available with BGTD option.
- Voltage selected utilizes a step-down transformer. Not available with L24 when ordered with N100. Not available with PS1050, E10WLCP or BGTD option.
- Requires SPD option.
- When continuous row mounting, fixtures must all have the same driver selection.
- Not available with Individual controls, nLight wired networking, nLight wireless networking, nLight wireless zone control options.
- Must specify voltage.
- Not available with L24 or L36. Not available with L48 in combination with N100.
- Available with L48 or L96 only. 20 Not available with PS1050 or E10WLCP options. Not available with 208 or 240V. Not available Individual controls, nLight Wired, or nLight Wireless options.
- Not available OUTEND.
- Required with PS1050, E10WLCP, BGTD, XAD, or XAD924.
- Not available with PLR options.
- Not available with Individual controls, nLight Wired, or nLight Wireless options.
- Sensor housing will be the same color as lens end caps.
- Not available with L24 in combination with 5000LM, not available with L36 in combination with 7500LM, not available with L48 in combination with 10000LM, and not available with L96 in combination with 14000LM, 18000LM, or 20000LM. Not available with PLRs containing low voltage dimming wires.
- Not available with any other control option. Requires EZ1.
- Requires N100 option.
- Ships standard as white.
- Not available with louver, wireguards, wide reflectors.
- More configurations on [LSXR Specification Sheet](#).
- L24 reflector is 22.65", L36 reflector is 34.01", L48 reflector is 46.80", L96 comes with two L48 reflectors.
- For use with L/LENS fixtures only. L24 reflector is 22.75", L36 reflector is 34.20", L48 reflector is 46.85", L96 comes with two L48 reflectors.
- Not for use with CLX wide reflector accessories.


OPTIONS AND ACCESSORIES



Narrow reflector
Ships separately from fixture.
Order as:
CLXRN24_ ____
CLXRN36_ ____
CLXRN48_ ____
CLXRN96_ ____




Wide decorative reflector
Ships separately from fixture.
Order as:
CLXRW24_ ____
CLXRW36_ ____
CLXRW48_ ____
CLXRW96_ ____



Wireguard
Ships separately from fixture:
96" fixture requires two WGCLX48.
Order as:
WGCLX24_ ____
WGCLX36_ ____
WGCLX48_ ____




Aircraft Cable with Canopy
Available in 120" or 240"
Order as:
ZAC120
ZAC240



HANGER CHAIN
36" chain with Y hanger. ships as a pair
Order as:
HC36



ZACVH HANGER
10' Aircraft cable with Y hanger.
Order as:
ZACVH



Tong hanger
Ships as a pair
Order As:
THCLX_ ____