

# MICROLINK 120VAC

## 120VAC Linkable Modular Seamless Bar Light

Modular, linkable, and now available in 120V AC. The MicroLink 120V AC fixture is a simple and versatile solution for new construction or remodeling applications. Streamline task and accent lighting with sleek, easy-to-install fixtures that brings style to any situation. Quick connect accessories make right angles, left angles, and cross connections easy work in complex installations.

- 3000K color temperature with 90+ CRI
- Low-profile fixture fits in a multitude of locations
- Available in four common size fixture lengths: 6" / 12" / 24" / 36"
- Lumen output up to 859Lm per fixture
- 65.6ft maximum link-ability
- Diffused lens for smooth, evenly distributed light
- Plug and play system for quick installation
- cETLus Listed for indoor, dry locations
- Suitable for use in closets based on NFPA 70, NEC section 410.16 (A) (3) and 410.16 (C)(5)

PROJECT:

TYPE:

LOCATION:


CATALOG NUMBER:




MICROLINK 120VAC QUICK SPECS	
VOLTAGE	120V AC
WATTAGE	2.4W / 4.8W / 9.6W / 14.4W
LUMENS	<859Lm
CCT	3000K
CRI	90+
MAX RUN	65.6ft (20 meters)
DIMMING	5-100%* with most standard 2-wire and CL dimmers
BEAM ANGLE	120°
OPERATING TEMP	-20°C (-4°F) to 45°C (113°F)
CERTIFICATIONS	cETLus Listed / JA8 Certified / indoor, dry locations
RATED LIFE	50,000 Hours

\*Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers.

MICROLINK 120VAC QUICK DIMENSIONS	
MLINK-120-30-6	6"
MLINK-120-30-12	12"
MLINK-120-30-24	24"
MLINK-120-30-36	36"



Top Profile



Side Profile

MICROLINK 120VAC ORDERING INFORMATION

ITEM NUMBER	CCT	LENGTH	LUMENS	WATTAGE	VOLTAGE	CRI	*DIMMING
MLINK-120-30-6	3000K	6"	130m	2.4W	120V AC	90+	CL / ELV (5-100%)
MLINK-120-30-12	3000K	12"	280Lm	4.8W	120V AC	90+	CL / ELV (5-100%)
MLINK-120-30-24	3000K	24"	565Lm	9.6W	120V AC	90+	CL / ELV (5-100%)
MLINK-120-30-36	3000K	36"	859Lm	14.4W	120V AC	90+	CL / ELV (5-100%)

MICROLINK 120VAC fixtures include: (1) MLINK-120-CONKIT, 4" mounting clips with screws (1 x for 6" & 12" / 2 x for 24" & 36", (1) End cap

MICROLINK 120VAC ACCESSORIES

ITEM NUMBER	DESCRIPTION
MLINK-120-CONKIT	6ft Power Connector Kit With Bare Wire
MLINK-120-CONKITP	6ft Power Connector Kit With Straight 120V AC Plug
MLINK-120-CONKITJ	6ft Power Connector Kit With Connector for use w/ ALSLBOX
MLINK-120-CONKITJ-15IN	15in Power Connector Kit With Connector for use w/ ALSLBOX
MLINK-120-L	"L" Connector LEFT
MLINK-120-R	"L" Connector RIGHT
MLINK-120-JUMP6	6in Jumper
MLINK-120-JUMP12	12in Jumper
MLINK-120-SPLICE	Linear light to Linear light splice connector
MLINK-120-CLIP	4in Aluminum mounting clip
ALSLBOX	Slimline Hardware Box - cETLus (Black Finish)
ALSLBOX-WH-B	Slimline Hardware Box - cETLus (White Finish)



MICROLINK 120VAC RECOMMENDED DIMMERS

BRAND	MODEL #
Lutron	DVCL-153P
Lutron	DVLV-600P
Lutron	DV-600P
Lutron	DVRF-6L
Lutron	RCL-153PNL
Lutron	MSCL-OP153M
Lutron	MACL-153ML
Lutron	CTCL-150
Lutron	CTCL-153P
Lutron	SCL-153P
Lutron	TGCL-153P
Lutron	STCL-153M
Lutron	STCL-153M
Leviton	IPL06
Leviton	DSL06
Leviton	6683

Dimmer performance may vary in field application due to unknown external factors. Dimmers not included on the chart above are not necessarily incompatible; they have yet to be fully evaluated. Please reference dimmer manufacturer's instructions for more detailed information regarding performance and compatibility. Test data listed above is based on single lamp data. Recommended maximum 10 units connected to a single dimmer.



# AMERICAN LIGHTING WARRANTY

## LIMITED WARRANTY FOR LED PRODUCTS: 5 YEARS

### LIMITED PRODUCT WARRANTY

Our products are warranted to be free from defects in material and workmanship for the warranty period listed. Warranty periods begin from the date of shipment from American Lighting Inc's warehouse to the original purchaser. Products that prove to be defective during their specific warranty period will be either repaired or replaced, at the sole discretion of American Lighting Inc. Claims for defective products must be submitted in writing to American Lighting Inc's RGA Department within the warranty period. Upon approval of such return, American Lighting Inc reserves the right to inspect the product for misuse or abuse. Claims for indirect or consequential damages or for product that, in American Lighting Inc's opinion, has been misused will be denied. This is a warranty of product reliability only and not a warranty of merchantability or fitness for a particular purpose. American Lighting Inc shall have no liability whatsoever in any event for payment of incidental or consequential damages, including, without limitations, installation costs and/or damages for personal injury and/or property. These products may represent a possible shock or fire hazard if improperly installed or altered in any way. This warranty does not apply to any product that has not been properly installed in accordance with current local codes and/or the National Electrical Code. Products that require a transformer, driver, or power supply must be used in conjunction with American Lighting Inc's recommended power supply to ensure safety and retain product warranty.

### PRODUCT SPECIFICATIONS

For the latest product information, updates, instructions and details concerning specifications, colors, finishes, performance, installation and design, visit [www.americanlighting.com](http://www.americanlighting.com).

Color may vary from the color printed herein due to limitations in photographic and printing processes. American Lighting Inc. reserves the right to change product specifications without notice. Other product specifications such as color temperature, wavelength characteristics and lumen output are subject to production limitations and may vary.

LED technology is changing rapidly, and not all color temperatures and performance levels can be duplicated at a later time. Best practices include purchasing 10-15% more for a particular project on the same initial order where white LED color temperatures must be maintained over project and product life. Eventual product replacement should be considered at layout and design stages. Best practices also include testing connections and product performance prior to mounting and/or installing.

### AVERAGE LIFE

Average incandescent lamp life, rated life and average life are terms used to describe the number of hours at which half of the lamps have failed. For LEDs, the hours of rated life specify the point where 70% of original lumen output is reached. Below this point, the effective life is over, however, the LED may still emit light. Individual results may vary with actual environmental conditions including, but not limited to, proper installation, ambient temperature and/or input voltage fluctuations.