

STL68 SERIES TAPE LIGHT

12V AC Submersible Standard Grade

Low voltage tape light for water features or wet location applications, the 12V AC Submersible tape is a highly sought after solution. With an IP68 outdoor submersible rating, our submersible tape can withstand most natural elements making for a great go to for small ponds and fountain lighting solutions.

- Available in 3000K color temperature
- Up to 90+ color rendering index
- 160Lm per foot
- Low energy consumption at 2.2W per foot
- IP68 submersible rating allows for water feature application
- Cuttable every 19.68" with a max run of 20'
- Dimmable (5-100%) with most ELV, TRIAC dimmers
- cULus Listed for outdoor wet locations
- 50,000 hours rated life

PROJECT:
TYPE:
LOCATION:
CATALOG NUMBER:



STL68 SERIES QUICK SPECS	
VOLTAGE	12V AC
WATTAGE	2.2W per foot
LUMENS	160Lm per foot
CCT	3000K
CRI	90+
MAX RUN	20ft (6m)
CUTTING POINTS	19.68"
IP RATING	IP68 - Encased
DIMMING	PWM (5-100%)
DIMENSIONS	13mm (0.51") W x 5.1mm (0.2") H
BEAM ANGLE	120°
OPERATING TEMP	5°C (41°F) to 70°C (158°F)
CERTIFICATIONS	cULus Listed - outdoor wet locations
RATED LIFE	50,000 Hours

STL68 SERIES IP RATINGS



IP68 (Encased)*

Fully encased tape light in silicone injected jacketing that allows for wet location applications.

Best suited: Indoor & Outdoor wet locations

*Not intended for long-term submersion nor submersion greater than 1M in depth. Not intended for use in swimming pools or other water features where humans and/or animals may enter the water. Not suitable for exposure to chemicals.

STL68 SERIES QUICK LOOK



HTL68 SERIES ORDERING INFORMATION

ITEM NUMBER	VOLTAGE	CCT	LENGTH	LUMENS / FT	WATTAGE / FT	IP RATING	CRI	CUTTING	MAX RUN
STL68-WW-16-12VAC	12V AC	3000K	16.4 ft	160Lm / ft	2.2W / ft	IP68	90+	19.68"	20 ft

Includes: Attached 1ft IP68 Power Feed with 6ft connector cable / Attached 1ft IP68 tail with 6ft connector cable / (15) "L" Mounting Clips / (2) IP68 End Caps

HTL68-RGB SERIES ACCESSORIES

ITEM NUMBER	DESCRIPTION
TL-2JUMP68-10	10ft Extension Cable (IP68)
TL-2JUMP68-20	20ft Extension Cable (IP68)
TL-CLIPS-15	Saddle Mounting Clips - Qty 15
TL-LCLIPS-15	"L" Mounting Clips - Qty 15



TL-2JUMP68-10
TL-2JUMP68-20



TL-CLIPS-15




TL-CLIPS-15



TL-LCLIPS-15

HTL68 SERIES TRIAC/ELV/MLV DIMMING WIRING DIAGRAM





AMERICAN LIGHTING WARRANTY

LIMITED WARRANTY FOR LED PRODUCTS: 5 YEARS

LIMITED PRODUCT WARRANTY

Our products are warranted to be free from defects in material and workmanship for the warranty period listed. Warranty periods begin from the date of shipment from American Lighting Inc's warehouse to the original purchaser. Products that prove to be defective during their specific warranty period will be either repaired or replaced, at the sole discretion of American Lighting Inc. Claims for defective products must be submitted in writing to American Lighting Inc's RGA Department within the warranty period. Upon approval of such return, American Lighting Inc reserves the right to inspect the product for misuse or abuse. Claims for indirect or consequential damages or for product that, in American Lighting Inc's opinion, has been misused will be denied. This is a warranty of product reliability only and not a warranty of merchantability or fitness for a particular purpose. American Lighting Inc shall have no liability whatsoever in any event for payment of incidental or consequential damages, including, without limitations, installation costs and/or damages for personal injury and/or property. These products may represent a possible shock or fire hazard if improperly installed or altered in any way. This warranty does not apply to any product that has not been properly installed in accordance with current local codes and/or the National Electrical Code. Products that require a transformer, driver, or power supply must be used in conjunction with American Lighting Inc's recommended power supply to ensure safety and retain product warranty.

PRODUCT SPECIFICATIONS

For the latest product information, updates, instructions and details concerning specifications, colors, finishes, performance, installation and design, visit www.americanlighting.com. Color may vary from the color printed herein due to limitations in photographic and printing processes. American Lighting Inc. reserves the right to change product specifications without notice. Other product specifications such as color temperature, wavelength characteristics and lumen output are subject to production limitations and may vary.

LED technology is changing rapidly, and not all color temperatures and performance levels can be duplicated at a later time. Best practices include purchasing 10-15% more for a particular project on the same initial order where white LED color temperatures must be maintained over project and product life. Eventual product replacement should be considered at layout and design stages. Best practices also include testing connections and product performance prior to mounting and/or installing.

AVERAGE LIFE

Average incandescent lamp life, rated life and average life are terms used to describe the number of hours at which half of the lamps have failed. For LEDs, the hours of rated life specify the point where 70% of original lumen output is reached. Below this point, the effective life is over, however, the LED may still emit light. Individual results may vary with actual environmental conditions including, but not limited to, proper installation, ambient temperature and/or input voltage fluctuations.