

orders

Date: Project:

Prepared for: Type:

Comments:

CANOPY LIGHT

before

3pm*.

1-10V DIMMABLE | ULTRA-THIN PROFILE



Arani

shipping

on













SPECIFICATIONS

Ultra-Thin Profile
Suitable for Wet Locations
Robust Die-Cast Aluminium Casing
Heat-Resistant Poly-Carbonate Lens
Colour Rendering Index: >80
Functioning Temperature:
-40°C to 40°C
Should only be installed
horizontally not on a wall

AVAILABILITY

1-10V Dimmable 100-277Vac / 347Vac 40W / 60W 4000K

*This icon indicates a STOCK item: Look for this Same Day Shipping icon below in 'Ordering Information' for products that ship on the same day (orders placed before 3pm)



Full IES File Available on Request

ORDERING INFORMATION

SERIES	INPUT VOLTAGE	POWER (WATTS)	EQUIVALENT TO (WATTS)	LUMENS	COLOR TEMP	PRODUCT ID	MODEL NUMBER	ORDERING CODE
CANOPY LIGHT	100-277Vac	40W	175W	5350	4000K	S-X6NZLT	CAN12R0027V40W-40KDDY-V5	CL-40W-40K-D-V5
		60W	250W	7800	4000K	S-4XP5AM	CAN12R0027V60W-40KDDY-V5	CL-60W-40K-D-V5
	347-480Vac	60W	250W	7800	4000K	S-JAU48Y	CAN12R0048V60W-40KDDY-V5	CL-60W-40K-D-V5-347V (2014)





Canopy Light





