



Arani is committed to same day shipping on orders before 3pm*.

GET YOUR PRODUCTS FAST

CEILING LIGHT

DIMMABLE | ENERGY STAR



5 Years



Lifetime
50 000 hours



IP20
Suitable for use in damp locations



Triac
Dimmable



SPECIFICATIONS

Surface Mounted

Built-in Driver

IP20 - Suitable for Damp Locations

Beam Angle: 110°

Colour Rendering Index: >80

Functioning Temperature: -20°C to 40°C

AVAILABILITY

24W

3000K / 4000K

120V



*This icon indicates a STOCK item:
Look for this Same Day Shipping icon below in 'Ordering Information' for products that ship on the same day (orders placed before 3pm)



Full IES File Available on Request



DIMMERS LIST

DIMMER	FLICKER?
ARANI DM1-150W-SL-3-WH-V2	NO
LEVITON 6672-1LW	NO
LEVITON DSL06-1LZ	NO
LEVITON 6674-P0W	NO
LEVITON IPL06-10Z	NO
LUTRON MACL-153MR-WH	NO
LUTRON SCL-153P-WH	NO
LUTRON CTCL-153P-WH	NO
LUTRON MSCL-OP153M-WH	NO
LUTRON DVCL-153P-WH	NO
LUTRON DVW-603PGH-WH	NO
LUTRON S-600P	NO
LUTRON S-600	NO

ORDERING INFORMATION

SERIES	POWER (WATTS)	EQUIVALENT TO (WATTS)	LUMENS	COLOUR TEMP	DIMENSIONS	INPUT VOLTAGE	MODEL NUMBER
12" CEILING LIGHT V3	24	120	1800	3000K	Ø12.00" x 0.55"	120V	CL12-24W-30K-WH-V3
			2000	4000K		120V	CL12-24W-40K-WH-V3