


Date:	Project:
Prepared for:	Type:
Comments:	


## **RESIDENTIAL OUTLETS**













## **SPECIFICATIONS**

Characteristics	<ul> <li>Back &amp; Side Wire</li> <li>Selfgrounding</li> <li>Residential Grade</li> <li>Tamper Resistant</li> </ul> 2 Years		
Input voltage	125Vac		
Rated Working Current	15A / 20A		
Maximum power	1875W (15A) / 2500W (20A)		
Environment	Suitable for Dry Locations.		
Wire size	#12- #14 AWG		
<b>Conductor Material</b>	Solid copper only		
Color Options	White / Black		
Weight	60g		
Material	Polycarbonate Body with Copper Contacts		
Warranty	2 Years		
Certifications	cULus		
Dielectric voltage	Withstands 2000V per UL498		
Flammability	Rated V-2 per UL94		
Operating Temperature	-40°C to 60°C		

## **ORDERING INFORMATION:**

<u>⊸</u> Stock item. Sam	e Day Shipping fo	or orders placed b	y 3pm EST
--------------------------	-------------------	--------------------	-----------

SERIES	RATED WORKING CURRENT	FINISH	ORDERING CODE
RESIDENTIAL OUTLETS	15A	WHITE	OU1-15A-TR-WH-V2 <del></del>
		BLACK	OU1-15A-TR-BK-V2 <del>-</del> - <del> </del>
	20A	WHITE	OU1-20A-TR-WH-V2*
		BLACK	OU1-20A-TR-BK-V2