



HYBRID SHOEBOX FLOODLIGHT V5

Our Hybrid Shoebox is crafted for efficiency and longevity it uses cutting-edge LED technology to bring light to outdoor spaces. Ideal for application in parking lots, streets, bustling commercial hubs, and sports arenas.

FEATURES & SPECIFICATIONS

TEATORES & STEEL TEATORS						
Electrical Caracteristics	 Input Voltage: 100-277Vac or 347-480Vac Power Selectable between: 40W/60W/80W/100W 72W/108W/144W/180W 120W/180W/240W/300W 					
IP Rating	• IP65: Suitable for wet locations					
Wire size of leads	• 18 AWG					
Length of leads	• 18"					
Colour Rendering Index	• 70+					
Colour Temperature	• CCT Selectable: 3000K/4000K/5000K					
Beam Spread	• Type 3					
Operating Temperatures	• -40°C to 40°C					
Dimmable	• 0-10V					
ЕРА	• 1 Fixture: 0.3632 • 2 Fixture @ 90°: 0.6849 • 2 Fixture @ 120°: 0.8861 • 2 Fixture @ 180°: 0.7264 • 3 Fixture @ 90°: 1.0481 • 3 Fixture @ 120°: 1.2078 • 4 Fixture @ 90°: 1.0481					
Materials	Die cast Aluminum Body Polycarbonate Lens					
Codes & Standards	• UL • DLC Premium CERTIFIED CERTIFIED PREMIUM					
Lifetime	• 100 000 hours					
Warranty	• 5 years					

OPTIONAL ACCESSORIES

(One accessory included with purchase)

Bracket for Shoebox



SH-BR-V5

Pole Mount for Shoebox



SH-WMA-V5

Slipfitter Mount for Shoebox



SH-SL-V5

ORDERING INFORMATION

Series	Power Selectable	Lumen Output	Colour Temperature	Input Voltage	DLC Product ID	Model Number	Ordering Code
Hybrid Shoebox Floodlight V5	40W 60W 14200lm	Selectable 3000K	100-277Vac	- S-T3C26A	S-T3C26A [Blank,P0,P3,P4	SHB12R0100W-[L,H]V-DDK-[D,B,W] [Blank,P0,P3,P4][Blank,M][SQ,SP,W-	SH-40W-100W-VAR-V5
	80W 100W		4000K 5000K	347-480Vac		M,YK,SQA]T3AD[Blank,A-Z,a-z,0-9]-V5	SH-40W-100W-VAR-V5 347V
	72W Selectable 108W 24000lm 3000K 144W at 180W 4000K 180W 5000K	Selectable 3000K	100-277Vac	S-YVBEF7	SHB12R0180W-[L,H]V-DDK-[D,B,W] [Blank,P0,P3,P4][Blank,M][SQ,SP,W- M,YK,SQA]T3AD[Blank,A-Z,a-z,0-9]-V5	SH-72W-180W-VAR-V5	
			347-480Vac			SH-72W-180W-VAR-V5-347V	
	120W Selectable 180W 41500lm 3000K 240W at 300W 4000K 300W 5000K		100-277Vac		SHB12R0300W-[L,H]V-DDK-[D,B,W]	SH-120W-300W-VAR-V5	
		347-480Vac	S-H2YQOL	[Blank,P0,P3,P4][Blank,M][SQ,SP,W-M,YK,SQA]T3AD[Blank,A-Z,a-z,0-9]-V5	SH-120W-300W-VAR-V5-347V		





OPTIONAL ACCESSORIES

(Sold Separately)

120-277V PIR Sensor



HB-PIR-V3

Microwave Sensor



HB-MS-V3

Photocell



SH-CELL-V3 SH-CELL-347