


Project:
Type:
Date:
Product Code:
Approval:



Durability, and cost-effective fluorescent lighting.

BFSP T5 - SPECIFICATIONS MAY CHANGE WITHOUT NOTICE

Contractor-grade, fluorescent surface and suspended mount strip fixture. It is ideal for indoor use, where energy-efficiency, performance and ease of maintenance is essential. Its rugged design and energy-efficiency make it ideally suited for task lighting or general illumination applications.

FEATURES

- 2', 3', 4' and 8' lengths available
- Available with 1, 2, 3, 4, 6 or 8 lamp configurations
- Optional wireguard allows added application flexibility
- Can be row mounted

OPTIONS

- 2', 3', 4' and 8' lengths available
- 1, 2, 3, 4, 6 or 8 lamps available
- Continuous row-mounting available
- 347V options available
- Wireguard with various finishes (consult factory)

APPLICATIONS

- Coves
- Display cabinets
- Manufacturing
- Task lighting

APPROVALS

- ETL listed product

OPTICS

Pre-painted body in high-reflectance white. T5 fluorescent light source is standard. Optional wireguard is available.

ELECTRICAL

All components have met all regulatory approvals. Fixture is available in 120 - 277VAC and 347V options. Lamp retention through rotary lamp holders.

MOUNTING


Holes provided for convenient surface mounting or S-hook chain-mounting. Can be row-mounted using a suspended or surface-mount configuration.

CONSTRUCTION

Pre-painted, high reflectance white body is precision bent for added strength and rigidity. End caps are fastened by screws allowing the flexibility of repositioning to act as joiners for raceway wiring. Shallow fixture design provides a clean appearance for many environments.



PRODUCT DIMENSIONS



PRODUCT KEY

Fixture Type	Fixture Size	Fixture Length	Number of Lamps	Lamp Watts	Lamp Type	Ballast Voltage	Ballast Factor	Options
BFSP				W				
	O (1.75W)	2'	1	28	T5	120	Normal (N)	
	M (2W)	3'	2	54	T5HO	120/277 (UNV)	High (H)	
	N (3W)	4'	3			347	Low (L)	
	Blank (5W)	8'	4					
			6					
			8					

OPTIONS

Battery Back-Up (Needs to be specified)	Wire W3XX - Flexible Whip - 16/3 600V White (XX - Length) W4XX - Flexible Whip - 16/3 600V Black (XX Length) W5XX - Power Cord (Twist Lock - Specify Nema Code) W6XX - Power Cord (3-Wire 120V Plug, 14/3)(XX - Length) W8XX - Power Cord (3-Wire 120V 5-15P, 16/3)	Lamp Wattage <table border="1"> <thead> <tr> <th rowspan="2">Length</th><th colspan="2">Nominal Lamp Watts</th></tr> <tr> <th>T5</th><th>T5HO</th></tr> </thead> <tbody> <tr> <td>24</td><td>14</td><td>24</td></tr> <tr> <td>36</td><td>21</td><td>39</td></tr> <tr> <td>48</td><td>28</td><td>54</td></tr> </tbody> </table>	Length	Nominal Lamp Watts		T5	T5HO	24	14	24	36	21	39	48	28	54
Length	Nominal Lamp Watts															
	T5	T5HO														
24	14	24														
36	21	39														
48	28	54														
Sensors W12 - Motion Sensor - 10C	Hangers M1 - Speedy Hanger (V-Bracket) M3 - Aircraft Cable "Y-Toggle", with cable gripper (5, 10 and 15')															
Wireguard G1 - Wireguard Heavy Duty, Painted White																