

Project:
Type:
Date:
Product Code:
Approval:



Flexibility, style and superior craftsmanship.

BFWC

Contractor-grade, surface and suspended mount fluorescent semi-wrap fixture. It is ideal for indoor use, where energy efficiency, performance and ease of maintenance is essential.

FEATURES

- Available in 4' or 8' lengths (custom sizes available)
- High-reflectance white steel reflector standard
- Available with 1, 2 or 3 lamp configurations
- T5 or T8 lamps
- K12 prismatic lens

OPTIONS

- 4', 8' and custom lengths available (consult factory)
- Reflectors available in pre-painted high-reflectance white steel, white aluminum and specular aluminum
- 1, 2 and 3 lamps available
- T5 or T8

APPLICATIONS

- Hospitals
- Offices
- Retail stores
- Schools

APPROVALS

- ETL listed product

OPTICS

Pre-painted body in high-reflectance white. Reflectors available in high-reflectance white steel, white aluminum and specularized aluminum. T5 and T8 light sources are available. Diffuser is a clear acrylic lens with a #12 prismatic pattern (standard).

ELECTRICAL

All components have met all regulatory approvals. Fixture is available in 120 - 277VAC and 347V options. Lamp retention through rotary lamp holders.

MOUNTING

Can be row-mounted using a suspended or surface-mount configuration. Holes provided for convenient surface mounting, aircraft cable or S-hook chain-mounting. V-shaped mounting brackets for suspended applications.


CONSTRUCTION

Pre-painted, high reflectance white body is precision bent for added strength and rigidity. Access panel and knock-outs make it ideal for through or standard wiring. Knock-outs provide easy through wiring for row-mounted applications.




PRODUCT DIMENSIONS

End View



Side View



PRODUCT KEY

Fixture Type	Fixture Size	Number of Lamps	Lamp Watts	Lamp Type	Ballast Voltage	Ballast Factor	Options
BFWC	<input type="text"/>	<input type="text"/> LP	<input type="text"/> W	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	4'	1	28	T5	120	Normal (N)	
	8'	2	32	T8	120/277(UNV)	High (H)	
		3	54		347	Low (L)	
		4					
		6					

OPTIONS

<p>Battery Back-Up (Needs to be specified)</p> <p>Lens L0 - No Lens Supplied L55 - Clear Acrylic Lens</p> <p>Wireguard G1 - Wireguard Heavy Duty, Painted White</p>	<p>Reflector R1 - Reflector - White Steel R2 - Reflector - Full - White Aluminum 92% R3 - Reflector - Full - Specular Aluminum 92%</p> <p>Sensors W12 - Motion Sensor - 10C W13 - Motion Sensor - 40C</p>	<p>Wire W1XX - Flexible Whip - 16/4 600V White (XX - Length) W2XX - Flexible Whip - 16/4 600V Black (XX - Length) W3XX - Flexible Whip - 16/3 600V White (XX - Length) W4XX - Flexible Whip - 16/3 600V Black (XX Length)</p> <p>Hangers M1 - Speedy Hanger (V-Bracket) M2 - Speedy Hanger & Aircraft Cable 5FT M4 - Aircraft Cable "V-Hanger", 18 Inch</p>
--	---	---

