

PERRY Ceiling Fan

part # CF48PER3ORB

CANARM LTD.

PO Box 367, 2157 Parkedale Avenue, Brockville, Ontario K6V5V6

Tel: 613-342-5424 | Fax: 1-800-263-4598

2555 Rue Bernard Lefebvre, Laval, Quebec H7C 0A5

Tel: 1-450-665-2535 | Fax: 1-450-665-1910

808 Commerce Park Drive, Ogdensburg, New York, USA 13669

Tel: 1-800-267-4427 | Fax: 1-800-263-4598

www.canarm.com

General

Size: 48"

Finish: oil rubbed bronze

Shade: alabaster glass

Glass size: 9" W x 3 1/8" H

Blades: 3 reversible blades medium maple & walnut

Blade pitch: 12°

Blade shape: flat tip

Lamping: 2 x 60W C bulbs (included)

Mounting: dual

Downrod (size): 4"

Lead wire (length): 48"

Motor Size: 153 x 11.5mm

Motor material: Copper, Metal, Aluminum

Limiter: 190W included

Remote Control: included

Switch housing cap: N/A

Capacitor: N/A

Country of Origin: China

Packaging

Color box: 23.27" x 10.05" x 13.23" (591 x 306 x 336mm)

Pieces per master: 1

Weight: 15.43 lbs

Warranty & Safety Standards

5 year warranty

cCSAus



Prepared for

Contact

Date

Presented by

Remarks

ENERGY INFORMATION at high speed

RENSEIGNEMENTS RELATIFS À L'ÉNERGIE à vitesse élevée

Airflow Débit d'air	Electricity use Consommation électrique	Airflow efficiency Rendement énergétique de débit d'air
4,328	42	103.05
Cubic feet per minute	Watts (excludes lights)	Cubic feet per minute per watt
Pieds cubes par minute	Watts (lumière exclues)	Pieds cubes par minute par watt

Compare: 36" to 48" ceiling fans have airflow efficiencies ranging from approximately 71 to 86 cubic feet per minute per watt at high speed
Comparaison: Les ventilateurs de plafond de 36" à 48" présentent un rendement énergétique du débit d'air approximativement compris entre 71 et 86 pieds cubes par minute par watt à vitesse élevée.

Money-saving tip: Turn off fan when leaving room.
Conseil d'économie d'argent: Éteindre le ventilateur en quittant la pièce.