

Mini Flood Light

15W | 4000K | 120-277V

Meet the successor to our best-selling FLM Mini Flood Lights!

Ideal for landscaping, patio, and security lighting, signs and building facades Excellent replacement for quartz halogen fixtures



TECHNICAL DATA





LIGHT SPECIFICATIONS

Lumens	1,856 lm
Efficacy	128.3 lm/W
CCT	4000K
Distribution	NEMA 7x7
CRI	82
Dimmable	0-10V
L70 Life	> 54,000 hrs
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
DLC	S-5VDWLB

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance				
Center Beam fc		Beam Wi	dth	
17.0R	2.37 fc	46.5 ft	49.9 ft	
34.0ft	0.59 fc	93.1 ft	99.8 ft	
51.0R	0.26 fc		149.7 ft	
68.0 R	0.15 fc	186.2 ft	199.6 ft	
85.0 R	0.09 fc	232.7 ft		
102.0R	0.07 fc	279.2 ft	299.3 ft	
■ Vert. Spread: 107.7° ■ Horiz. Spread: 111.5°				

DIMENSIONAL DRAWING (IN)



ELECTRICAL

Wattage	15W
Voltage	120-277V
Current	0.15A
Surge Protection	2.5kV
Auxiliary Output	N/A
Power Factor	0.9
THD	15%
Operating Temp	-30°C to 45°C

CONSTRUCTION

Cord Whip	19.7"
Housing	Die-Cast Aluminum
Finish	Polyester Powder Coat
Finish Colour	Bronze
IP Rating	IP65

DIMENSIONS

Fixture Weight	1.05 lbs
Fixture Dimensions	5.9" x 4.4" x 1.6"
Carton Qty	1
Carton Weight	1.5 lbs
Carton Dimensions	6.5" x 2.4" x 8.9"
Master Carton Qty	16
Master Carton Weight	25.4 lbs
Master Carton Dimensions	19.9" x 13.7" x 9.6"

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

