

WPX Wall Pack

120W | Colour Selectable | 120-347V



The most versatile architectural wall pack in Canada
Ideal for outdoor wall-mount applications such as commercial,
industrial, retail, or hospitality buildings

Type III Distribution
Optics Standard

Type II and Type IV
options available

Durable Die-Cast
Aluminum Housing



Also available
in Black



1/2" NPT Entry
on all sides



Certified by DarkSky.org

Approved by DarkSky
when set for 3000K operation

Colour Selectable
3000K/4000K/5000K

120-347V Driver
with 6kV
surge protection



TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	14,499 lm
Efficacy	120.2 lm/W
CCT	3000K / 4000K / 5000K
CRI	73
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	10-year
Factory Settings	120W 5000K

APPROVALS AND LISTINGS

cETL	5018387
DLC Premium	PLACD7STWCD0

ACCESSORIES (Ordered Separately)

Visor	WPX-VISOR-S-WH
Type II Optics	WPX-T2S
Type IV Optics	WPX-T4S
Photocell (0-10V)	HD06VCRH (Photocell and Receptacle)
Motion Sensor (0-10V)	HB01DMS-C (Multifunction Motion and Daylight)

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance			
	Center Beam fc	Beam Width	
4.0ft	113.5 fc	3.7 ft	8.4 ft
8.0ft	28.4 fc	7.4 ft	16.7 ft
12.0ft	12.6 fc	11.2 ft	25.1 ft
16.0ft	7.1 fc	14.9 ft	33.5 ft
20.0ft	4.5 fc	18.6 ft	41.8 ft
Vert. Spread: 49.9° Horiz. Spread: 92.6°			

ELECTRICAL

Wattage	120W
Voltage	120-347V
Power Factor	0.96
Current	1.6A
THD	6.5%
Operating Temp	-40 to 45°C
Operating Temp (with Sensor)	-20 to 45°C

CONSTRUCTION

Housing	Die-Cast Aluminum
Cover	Polycarbonate
Finish	Powder Coat
Finish Colour	White
IP Rating	IP65

DIMENSIONS & WEIGHTS

Fixture Weight	5.85 lbs
Fixture Dimensions	11 x 9.2 x 7.2 in
Carton Qty	1
Carton Weight	7.55 lbs
Carton Dimensions	12.2 x 10.8 x 8.5 in

DIMENSIONS

