

---

## Ultra-slim puck

Thanks to its 1/4" profile, our 12V ultra-slim LED pucks can be integrated onto any surface. Available as a single unit or as a kit of 3. The choice is yours!



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
<b>4006</b>	Ø3.875"	3.6 W	250 lm	90	3000 K	12 V

### Specifications

12V DC LED driver required (4006/4006SQ)  
 Over 50,000 hours of service life  
 12" input lead with quick connector  
 24" interconnection harness included  
 Warm white light output  
 Superior LED performance and lifespan  
 Smooth 360° wide spread  
 Minimal heat emission  
 Heat sink and thermal protection  
 JA8 Certified  
 Refer to website for dimmer compatibility  
 5-year warranty

### Note

Plug-in or hard-wired power supply required for installation when purchasing the single unit (4006). Sold separately.

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALs representative for more information.

### Power supplies: plug-in

**ETR-LED10WPI**  
 12V DC/10W class 2 LED driver  
**ETR-LED24WPI**  
 12V DC/24W class 2 LED driver

### Power supplies: hard-wired

**DD1260**  
 LED driver and dimmer in one unit  
**BT06DIM-IC**  
 6W dimmable LED hardwire driver  
**BT12DIM-IC**  
 12W dimmable LED hardwire driver  
**BT24DIM-IC**  
 24W dimmable LED hardwire driver  
**BT36DIM**  
 36W dimmable LED hardwire driver  
**BT48DIM**  
 48W dimmable LED hardwire driver

### Finish

● **BK** Black  
 ● **SN** Satin Nickel  
 ○ **WH** White

### Accessories

**4000-E24**  
 24" extension cord  
**4000-E60**  
 60" extension cord  
**4000HRNS-24**  
 24" interconnection harness  
**4006-TRIM-BK**  
 Decorative trim in black  
**4006-TRIM-SN**  
 Decorative trim in satin nickel

4006

