


# MINI-PUCK

Enjoy complete flexibility with our mini LED pucks. Feel free to recess, surface mount, or direct-wire these directional pucks to achieve your desired lighting effect.



LEDRDM1

Ø1.75"



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
LEDRDM1	Ø2"	1.1 W	80 lm	80	3000 K	12 V

## Specifications

- 12V DC LED driver required
- 12" input lead with quick connector
- 24" interconnection harness included
- Smooth 360° wide spread
- Can be recessed or surface mounted
- Surface adapter included
- Gimbal LED module
- 5-year warranty

## Power supplies: plug-in

- ETR-LED10WPI**  
12V DC/10W class 2 LED driver
- ETR-LED24WPI**  
12V DC/24W class 2 LED driver

## Power supplies: hard-wired

- DD1260**  
LED driver and dimmer in one unit
- BT06DIM-IC**  
6W dimmable LED hardwire driver
- BT12DIM-IC**  
12W dimmable LED hardwire driver
- BT24DIM-IC**  
24W dimmable LED hardwire driver
- BT36DIM**  
36W dimmable LED hardwire driver
- BT48DIM**  
48W dimmable LED hardwire driver

## Finish

- BK** Black
- SBA** Sandblasted aluminum
- WH** White

## Accessories

- 4000-E24**  
24" extension cord
- 4000-E60**  
60" extension cord
- 4000HRNS-24**  
24" interconnection harness

## Note

Plug-in or hard-wired power supply required for installation. Sold separately. Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALIS representative for more information.