

Date:	Fixture:
Qty:	Client/ Project:



DelSnap

Metric Troffer

FEATURES

- Steel construction
- Frosted lens
- Easy Lay-in installation
- 5 size options
- General ceiling light applications

10 Year
Warranty

SPECIFICATIONS

Efficacy:
116 Lm/W

CRI:
83+

Color Temperature:
3000K, 3500K, 4000K, 5000K

Lumen Maintenance:
180,000+ Life Hours (L70)

Voltage:
120/277V | 347V

Control Options:
0-10V Dimming,
WiFi Dimmable

Operating Temperature:
-40°C to +40°C

Mounting Options:
T Bar

Wiring Options:
Black and White Flexible
Cord

Accessories:
Occupancy Sensor
10kV Surge Protection

OUTPUT PERFORMANCE

Model	Watts	Lm/W	Delivered Lumens
300 x 300	20	116	2,320
300 x 300	30	116	3,480
300 x 300	40	116	4,640


Model	Watts	Lm/W	Delivered Lumens
300 x 1200	20	116	2,320
300 x 1200	30	116	3,480
300 x 1200	40	116	4,640
300 x 1200	60	116	6,960

Model	Watts	Lm/W	Delivered Lumens
300 x 1500	30	116	3,480
300 x 1500	40	116	4,640
300 x 1500	60	116	6,960


Model	Watts	Lm/W	Delivered Lumens
500 x 1200	20	116	2,320
500 x 1200	30	116	3,480
500 x 1200	40	116	4,640
500 x 1200	60	116	6,960

Model	Watts	Lm/W	Delivered Lumens
500 x 1500	20	116	2,320
500 x 1500	30	116	3,480
500 x 1500	40	116	4,640


DIMENSIONS





300mm x 300mm




300mm x 1200mm




300mm x 1500mm



500mm x 1200mm



500mm x 1500mm



ORDERING GUIDE

MODEL	WATTS	COLOR TEMP	VOLTAGE	LENS	FINISH	MOUNTING
DelSnap 300x300	20,30,40	3K 3000K	U 120/277V	NL Normal Frosted Lens (standard)	WH White	T BAR T Bar
DelSnap 300x1200	20,30,40,60	35K 3500K	H 347V			
DelSnap 300x1500	30,40,60	4K 4000K 5K 5000K				
DelSnap 500x1200	20,30,40, 60					
DelSnap 500x1500	20,30,40					
				NL	WH	T BAR

WIRING	ACCESSORIES	PLUG
BFC Black Flexible Cord	N None	N None
WFC White Flexible Cord	OCC Occupancy Sensor (on/off)	*See Plug Options
	10kV 10kV Surge Protection	

NOTE

OCC - Consult Factory

PLUG OPTIONS

5-15P - 125V 15A T-Slot Plug
L5-15P - 125V 15A Locking Plug
5-20P - 125V AC 20A T-Slot Plug
L5-20P - 125V 20A Locking Plug
6-15P - 250V AC 15A 3W/2P Plug NEMA 6-15
L6-15P - 250V 15A Locking Plug
6-20P - 250V AC 20A Plug
L6-20P - 250V 20A Locking Plug
7-15P - 277V 15A 3W/2P NEMA 7-15 Plug
L7-15P - 277V 15A Locking Plug
7-20P - 277V AC 20A Plug
L7-20P - 277V 20A Locking Plug
24-20P - 347V AV 20A 3W/2P Plug NEMA 24-20
L24-20P - 347V 20A Locking Plug
24-15P - 347V AC 15A 3W/2 Plug NEMA 24-15