



Date: _____ Fixture: _____
QTY: _____ Project: _____



Arius LB

Low Bay Surface Mount

Low profile surface mount lighting. Side spill and down light distribution options. Polycarbonate protective lens. Occupancy sensor, Bi-level dimming, Photo control, and 10kV surge protection options. Commercial, industrial, and outdoor applications. DLC Listed. 10 Year Warranty.

Performance

Model	Distribution	Watts	Lm/W	Delivered Lumens
Arius LB 40	Side Spill	40	99.2	3,967
Arius LB 60	Side Spill	57	92.2	5,256

Model	Distribution	Watts	Lm/W	Delivered Lumens
Arius LB 40	Down Light	40	110	4,400
Arius LB 60	Down Light	57	110	6,270

Ordering Options

MODEL	WATTS	COLOR TEMP	VOLTAGE	LENS	DISTRIBUTION	FINISH	MOUNTING
Arius LB	40 60	3K 3000K 35K 3500K 4K 4000K 5K 5000K	U 120/277V H 347V	CL Clear	SS Side Spill DL Down Light	WH White BLK Black	FM Flush Mount ST Stem

Arius LB				CL			
----------	--	--	--	----	--	--	--

WIRING	ACCESSORIES	PLUG OPTIONS
BFC Black Flexible Cord WFC White Flexible Cord	N None OCC Occupancy Sensor (on/off) BLD Bi Level Dimming (100%/10%) PC Photo Control 10kV 10kV Surge Protection	N None *See Plug Options

--	--	--	--

SAMPLE: ARIUSLB - 40 - 4K - U - CL - SS - WH - FM - BFC - N - N

PLUG OPTIONS

5-15P - 125V 15A T-Slot Plug	L6-15P - 250V 15A Locking Plug	7-20P - 277V AC 20A Plug
L5-15P - 125V 15A Locking Plug	6-20P - 250V AC 20A Plug	L7-20P - 277V 20A Locking Plug
5-20P - 125V AC 20A T-Slot Plug	L6-20P - 250V 20A Locking Plug	24-20P - 347V AV 20A 3W/2P Plug NEMA 24-20
L5-20P - 125V 20A Locking Plug	7-15P - 277V 15A 3W/2P NEMA 7-15 Plug	L24-20P - 347V 20A Locking Plug
6-15P - 250V AC 15A 3W/2P Plug NEMA 6-15	L7-15P - 277V 15A Locking Plug	24-15P - 347V AC 15A 3W/2 Plug NEMA 24-15

Specifications subject to change without notice.

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Product Details

Specifications

Efficacy: Side Spill: Up to 99 Lm/W | Down Light: 110 Lm/W
 CRI: 83
 Color Temperature: 3000K, 3500K, 4000K, 5000K
 Lumen Maintenance: 180,000+ Life Hours (L70)
 Voltage: 120/277V | 347V
 Watts: 40W, 60W
 Controls: 0-10V Dimming
 Operating Temperature: -20°C to +35°C | 40°C to +35°C - available


Mounting

Flush Mount, Stem


Accessories

Occupancy Sensor (on/off)
 Bi Level Dimming (100%/10%)
 10kV Surge Protection
 Photo Control

Photometrics





Arius LB 40
Side Spill Distribution




Arius LB 60
Side Spill Distribution

Dimensions



Distribution side



Mounting Side