



Date: _____ Fixture: _____

QTY: _____ Project: _____



TitanHB 160-320

High Bay

LED high bay luminaire. Aluminum construction with polycarbonate protective lens.

Dry and Damp rated. Natatorium option available. Driver accessible drawer.

Commercial, industrial, sports arenas, sport complex and gymnasium applications.

DLC and cULus listed. 10 Year Warranty.

Output Performance

Model	Watts	Lm/W	Lumens
TitanHB 160	159	126.1	20,048
TitanHB 320	318	119.2	37,912

Ordering Options

MODEL	WATTS	COLOR TEMP	VOLTAGE	LENS	FINISH	MOUNTING
TitanHB	160 320	3K 3000K 35K 3500K 4K 4000K 5K 5000K	U 120/277V H 347/480V	FR Frosted CL Clear CLG Clear Glass	WH White CU Custom	V V Hook JC72 Jack Chain Set 4 X 72" w/ "S" hooks included JC96 Jack Chain Set 4 X 96" w/ "S" hooks included JC144 Jack Chain Set 4 X 144" w/ "S" hooks included ACY120 Aircraft Cable 120" W/Y Toggles & Adjusters ACY200 Aircraft Cable 200" W/Y Toggles & Adjusters

TITAN HB						
----------	--	--	--	--	--	--

MOUNTING (CONT.)	WIRING	ACCESSORIES	PLUG OPTIONS
MS3-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 3' threaded at both ends MS4-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 4' threaded at both ends MS6-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 6' threaded at both ends MS8-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 8' threaded at both ends 1/2 NPT Diecast Mounting Plate with 1/2" NPT 3/4 NPT Diecast Mounting Plate with 3/4" NPT IND Indirect-Uplight mounting bracket *TG T-Grid (Kit)	BFC Black Flexible Cord WFC White Flexible Cord	N None OCC Occupancy Sensor (on/off) *WC Wireless Controls BLD Bi Level Dimming (100%/10%) GCC Gasketed and Conformal Coated DA Dimming Wire Accessible 10kV 10kV Surge Protection	N None *See Plug Options

--	--	--	--

SAMPLE: TITANHB - 160 - 4K - U - FR - WH - V - BFC - N - N

TG - TitanHB 160 with recessed kit specification sheet or consult factory

WC - Please consult factory

TitanHB Natatorium - includes conformal coated boards and gasketing for damp and chlorine rated environments

PLUG OPTIONS

5-15P - 125V 15A T-Slot Plug

L5-15P - 125V 15A Locking Plug

5-20P - 125V AC 20A T-Slot Plug

L5-20P - 125V 20A Locking Plug

6-15P - 250V AC 15A 3W/2P Plug NEMA 6-15

L6-15P - 250V 15A Locking Plug

6-20P - 250V AC 20A Plug

L6-20P - 250V 20A Locking Plug

7-15P - 277V 15A 3W/2P NEMA 7-15 Plug

L7-15P - 277V 15A Locking Plug

7-20P - 277V AC 20A Plug

L7-20P - 277V 20A Locking Plug

24-20P - 347V AV 20A 3W/2P Plug NEMA 24-20

L24-20P - 347V 20A Locking Plug

24-15P - 347V AC 15A 3W/2 Plug NEMA 24-15

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Specifications subject to change without notice.

Product Details

Specifications

Efficacy: Titan HB 160:126 Lm/W | Titan HB 320: 119 Lm/W
CRI: 86
Color Temperature: 3000K, 3500K, 4000K, 5000K
Lumen Maintenance: 200,000+ Life Hours (L70)
Voltage: 120/277V | 347/480V
Operating Temperature: -25°C to +40° | -25°C to +55° - option available

Controls

0-10V Dimming, Wifi, Occupancy Sensor, Bi-Level Dimming


Mounting

V Hook, Jack Chain, Aircraft Cable, Mounting Stem, Diecast Mounting Plate, Indirect-Uplight Mounting Bracket

Accessories

Gasketed and Conformal Coated, Dimming, Wire Accessible, 10kV Surge Protection

Dimensions



Specifications subject to change without notice.