







Date:	Fixture:	
OTY:	Project:	



## **Zoom Eco**

## High Bay

Heavy duty construction. One piece die cast aluminum fixture provides maximum heat dissipation. Cooling fins added to increase the ambient temperature to 50°C standard. Built in heat sink. Quick disconnected cable feature quickly separates the driver from the LED module for easy maintenance. Retail, industrial, commercial, and architectural applications. 10 Year Warranty.

## **Ordering Options**

MODEL	WATTS	COLOR TEMP	VOLTAGE	LENS	FINISH	MOUNTING
Zoom Eco	150 180 240	<b>5K</b> 5000K	<b>U</b> 120/277V	FL Flat Lens AL Aluminum Reflector AC Acrylic Reflector	<b>WH</b> White	H Hook PM Pendant Mount
ZOOM ECO		5K	U		WH	
CORD COLO	PR	ACCESSORIES				
BFC Black Flexible Cord WFC White Flexible Cord		FG Flat Glass CLF 16" Conical Lens CLD 16" Conical Lens WG Wire Guard				

**SAMPLE:** ZOOMECO - 150 - 5K - U - FL - WH - H - BFC - FG

Voltage - Please consult factory for additional voltages Finish - Please consult factory for additional finishes

Specifications subject to change without notice.



## **Product Details**

### **Specifications**

Efficacy: Up to 136 Lm/W

CRI: 70+

Color Temperature: 5000K

Lumen Maintenance: 75,000+ Life Hours (L70)

Voltage: 120/277V

Operating Temperature: -40°C to +50°C

## Mounting

Pendant, Hook

#### Accessories

16" Flat Glass

16" Conical Lens

16" Deep - Conical Lens


16" Wire Guard

## **Output Performance**

Model	Watts	Lm/W	Lumens
Zoom Eco 150	150	132	19,800
Zoom Eco 180	180	136	24,480
Zoom Eco 240	240	129	30,960

8.26"

## **Dimensions**





Zoom Eco 150W














13.4"

Zoom Eco 180W, 240W

Specifications subject to change without notice.



# **Lens Options**







Acrylic Reflector

**Aluminum Reflector** 

Flat Glass


NOTE: Black Finish- Please consult factory

## **Accessories**









16" Flat Glass with Clamp Band

16" Flat - Conical Lens with Clamp Band

16" Deep - Conical Lens with Clamp Band

16" Wire Guard

Specifications subject to change without notice.