

SPECIFICATION SHEET

SUBJECT

LED CEILING LIGHT

CUSTOMER PROJECT

Project: _____
 Type: _____
 Cat. No.: _____
 Qty: _____
 Date: _____
 EEL Rep: _____



solutions closer to nature

Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872



DESCRIPTION

From the simple and functional design of our low profile ceiling lights to the decorative clean flush mount, each fixture is of the best quality and easy to clean.

SPECIFICATION FEATURES

Construction

Flush mount steel housing painted white, white acrylic lens
 2 sizes: 11-inch and 14-inch
 Rounded or straight edge profile

Electrical

Long life LED system complete with electrical driver to deliver the optimal performance
 LED's available in 3000K with typical CRI: 80
 Dimmable
 Ambient temperature -40°C to 40°C
 LED modules rated for 50,000 hours
 Electronic drivers are available in 120 or 120/277 volt applications

Driver and Module Access

Driver and modules can be accessed by turning the lens, no tools required

Mounting

Surface Mount

Finish

Galvanized steel for durability and a powdered high gloss paint finish

Shielding

White acrylic diffuser

Compliance


cULus (CL-T6113 & CL-T6213)
 cETLus & Energy Star (CL-A6111 & CL-A6211)

Warranty


5 years




**LED
CEILING LIGHTS**
11 inch and 14 inch




CL-A6111-6-LED02
Dimensions
 mm | 279(D) x 95(H)
 inch | 11(D) x 3.8(H)



CL-T6113-6-LED03
Dimensions
 mm | 356(W) x 89(H)
 inch | 14(W) x 3.5(H)



CL-A6211-6-LED02
Dimensions
 mm | 279(D) x 76(H)
 inch | 11(D) x 3(H)



CL-T6213-6-LED03
Dimensions
 mm | 356(W) x 97(H)
 inch | 14(W) x 3.8(H)





ORDERING CODE, ENERGY AND PERFORMANCE DATA

	Model No.	Delivered Lumens (lm)	Input Watts (W)	Voltage (V)	Colour Temp. (K)	Efficacy (lm/W)	Certification	Type
	CL-A6111-6-LED02 11 inch Round Edge Dimmable	1150	15	120	3000K	77		Standard
	CL-T6113-6-LED03 14 inch Round Edge - Limited Qty -	1106	14	120-277	3000K	79		
	CL-A6211-6-LED02 11 inch Straight Edge Dimmable	1150	15	120	3000K	77		Special Order
	CL-T6213-6-LED03 14 inch Straight Edge - Limited Qty -	1148	14	120-277	3000K	82		

NOTE:
Lumens are Estimated

CONTROLS (OPTIONAL):

ULT - HC419S | On-Off Sensor Control | 120-277V (applies to CLA6111/ CL A6211 only)
ULT - HC419V | Tri-level Dimming Control | 120-277V

