

Ceiling Light Nimbus

CUSTOMER PROJECT

Project: _____
 Type: _____
 Cat. No.: _____

 Qty: _____
 Date: _____
 EEL Rep: _____



Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872

DESCRIPTION

The Nimbus Series offers the familiar look and feel of a traditional ceiling light. Paired with a glossy polystyrene shield and SPCC cold rolled steel, this is a durable and reliable option. The Nimbus Series is also triac-dimmable and 3CCT-B selectable.

SPECIFICATION FEATURES

Construction

- SPCC Cold Rolled Steel + Polystyrene shielding
- Available in 11" and 14"

Controls

- Built-In Linear Driver

Mounting

- Surface Mount

Finish

- White

Compliance

- Energy Star
- ETL
- Suitable for damp locations

Warranty

- 5-Year Warranty (Standard)
- 10-Year Limited Warranty (Optional)



Ceiling Light Nimbus

NIMBUS SERIES

Wattage(s)	20W, 26W
Voltage	120V
Dimmable	Triac Dimmable
CCT	3CCT-B (3000K, 4000K, 5000K)
CRI	90+
Lumen Maintenance	L70 = 30,000h
Operating Temperature	-20°C to 40°C
Beam Angle	115°
PF	0.9

ORDERING CODE, ENERGY AND PERFORMANCE DATA

Model No.	Delivered Lumens (lm)	Input Watts (W)	Voltage (V)	Colour Temp. (K)	CRI	Efficacy (lm/W)	Certification	Type
 CLNB-337R11 20W120V-3CCTB-Triac-CRI90	1440	20W	120V	3CCT-B	90+	72	 Standard (Pending)	
 CLNB-537R14 26W120V-3CCTB-Triac-CRI90	1820	26W	120V	3CCT-B	90+	70	 Standard (Pending)	

NOTE:
 • Lumens are estimated

