



# EXIT/EMERGENCY

## FEATURES

- Easy to install
- Long battery life
- Environmentally friendly
- Energy saving
- Single or double-sided installation

## LISTINGS

- UL Listed for Dry/Damp locations
- Safety and performance in accordance with UL-924

## PERFORMANCE

- ≥90 minutes of emergency operating power at the rated wattage

## ELECTRICAL SPECIFICATIONS

- Input voltage: 120/347V
- Input power: 3W
- Power Factor: >0.5
- Emergency operation: ≥90 mins
- Recharge: 24 hrs

## THERMAL

- 32°F to 104°F (0°C to 40°C) operating temperature

## CONSTRUCTION

- Injection molded ABS and polycarbonate housings

## WARRANTY

- 3 year limited warranty; see eiko.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



EXIT/CA



EXIT/EM/CA

Included Faceplates:



## APPLICATIONS

- Emergency and exit lighting

RoHS  
Compliant

FC

cUL  
LISTED

## ORDERING INFORMATION

EXAMPLE: EXIT/EM-R-BK

Model
EXIT/CA - Exit Sign
EXIT/EM/CA - Exit Sign with Emergency Light

PERFORMANCE SUMMARY

Order Code	Item #	Description
11049	EXIT/CA	Exit Sign (Canada)
11050	EXIT/EM/CA	Exit Sign with Emergency Light (Canada)

DIMENSIONS

