



# F25T8/830K



|                      |                                                    |
|----------------------|----------------------------------------------------|
| <b>Description</b>   | 25W Universal Start 3000K 85 CRI T-8 Medium Bi-pin |
| <b>Ordering Code</b> | 49581                                              |
| <b>UNSPSC Code</b>   | 39101605                                           |

## Specifications

|                                  |                                 |
|----------------------------------|---------------------------------|
| <b>Watts</b>                     | 25                              |
| <b>Base Type</b>                 | G13                             |
| <b>Bulb Type</b>                 | T8                              |
| <b>MOL in/mm</b>                 | 36.0/915                        |
| <b>Length</b>                    | 3'                              |
| <b>MOD in/mm</b>                 | 1.0/26                          |
| <b>Mercury Content (mg)</b>      | 3                               |
| <b>HG Form</b>                   | solid                           |
| <b>Approx Initial Lumens</b>     | 2225                            |
| <b>Approx Mean Lumens</b>        | 2050                            |
| <b>CT deg K</b>                  | 3000                            |
| <b>CRI</b>                       | 85                              |
| <b>Avg Life 3 HR Inst Start</b>  | 20,000                          |
| <b>Avg Life 12 HR Prog Start</b> | 25,000                          |
| <b>Special Desc</b>              | Three Phosphor, Universal Start |
| <b>Approvals</b>                 | IMERC, TCLP Compliant           |

[watch](#) > [like](#) > [follow](#)



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335