

LED T8 U-Bend Direct Fit : 1-5/8"



11.5
watts

1,800
lumens

>156
lpw

50,000
hours

Features

- Directly replaces fluorescent U1 lamps
- No socket changes, uses shunted or non-shunted sockets
- Operates on most electronic T8 (instant & programmed), and dimming ballasts
- Instantaneous full light output upon power-up
- Choice of 3000K, 3500K, 4000K, or 5000K CCT
- Frosted glass lens reduces visual glare
- Environment-friendly, no mercury or lead
- 5 year product warranty
- Suitable for use in totally enclosed fixtures
- No rewiring or modifications of any kind required



Performance

- 11.5W replaces 32W fluorescent
- 1,800 lumens @ 11.5W
- Power factor: ≥ 0.9
- 82+ CRI
- 50,000 hour life

Applications

- Highbays
- Troffers
- Industrial Strips
- Cove Lighting
- Warehouses
- Stairwells
- Cold Storage



LED T8 U-Bend Direct Fit : 1-5/8"

Dimensions



Ordering Information

Order Code	Item #	W	Lm	CCT	CRI	MOL	Base	Life/Hrs	Replaces Fluor.	DLC
10094	LED11.5WT8F/U1/835-G8DR	11.5W	1,800	3500K	82+	2.24\"/>570mm	G13	50K	32W Fluorescent	✓
10095	LED11.5WT8F/U1/840-G8DR	11.5W	1,800	4000K	82+	2.24\"/>570mm	G13	50K	32W Fluorescent	✓
10096	LED11.5WT8F/U1/850-G8DR	11.5W	1,800	5000K	82+	2.24\"/>570mm	G13	50K	32W Fluorescent	✓

NOTE: Use order code when ordering.

✓ DesignLights Consortium® Qualified

watch > like > follow



23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 · (F) 1.800.492.8975
Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 · (F) 1.888.705.1335