

LED T8 Direct Fit Replacement Lamps



12-15
watts

1,800-
2,200
lumens

up to
150
lpw

universal
burn

Features

- Directly replaces all 4ft F32T8 (32W) lamps
- No socket changes, uses shunted or non-shunted sockets
- Operates on most electronic T8 (instant & programmed) ballasts
- Instantaneous full light output upon power-up
- Choice of 3500K, 4000K, or 5000K CCT
- NSF listed for commercial foodservice equipment
- Frosted glass lens reduces visual glare
- Environment-friendly, no mercury or lead
- 5 year product warranty
- Suitable for use in totally enclosed fixtures
- No rewiring or modifications of any kind required



Performance

- 4': 1800 lumens @ 12W
- 4': 2200 lumens @ 15W
- 80 CRI
- Beam Angle: 220°
- THD: <20%
- Power Factor: 0.98
- Rated Lifetime: 50,000 hours @ L70
- UL listed for damp locations
- Suitable for use in fixtures where ambient temperature is between -4°F (-20°C) and 113°F (45°C)
- Does not operate on magnetic ballasts
- Does not operate on T12 ballasts
- Visit eiko.com to view complete ballast compatibility information

Applications

- Highbays
- Troffers
- Industrial Strips
- Cove Lighting
- Vapor Tights
- Warehouses
- Stairwells
- Cold Storage



LED T8 Direct Fit Replacement Lamps

Photometrics



NSF offers the most accepted and trusted certification and verification programs for commercial foodservice equipment, specified by health departments, restaurant buyers and specifiers worldwide. NSF means market access – products with the NSF mark receive guaranteed regulatory acceptance in North America and improved acceptance worldwide. Verification programs, such as HACCP Compliance Verification - EU, demonstrate hygienic quality, independently verified by a trusted source.

Ordering Information

| Order Code | Item # | Length | Lm | Nominal W | V (Ballast Dependent) | CCT | CRI | Glass Tube | Bm | Life/Hrs | DLC |
|--------------|----------------------|--------|-------|-----------|-----------------------|-------|-----|------------|------|----------|-----|
| 09931 | LED12WT8/48/835-G8DR | 4' | 1,700 | 12W | 120-277V, 347V | 3500K | 80+ | Frosted | 220° | 50K | ✓ |
| 09932 | LED12WT8/48/840-G8DR | 4' | 1,800 | 12W | 120-277V, 347V | 4000K | 80+ | Frosted | 220° | 50K | ✓ |
| 09933 | LED12WT8/48/850-G8DR | 4' | 1,800 | 12W | 120-277V, 347V | 5000K | 80+ | Frosted | 220° | 50K | ✓ |
| 09934 | LED15WT8/48/835-G8DR | 4' | 2,100 | 15W | 120-277V, 347V | 3500K | 80+ | Frosted | 220° | 50K | ✓ |
| 09935 | LED15WT8/48/840-G8DR | 4' | 2,200 | 15W | 120-277V, 347V | 4000K | 80+ | Frosted | 220° | 50K | ✓ |
| 09936 | LED15WT8/48/850-G8DR | 4' | 2,200 | 15W | 120-277V, 347V | 5000K | 80+ | Frosted | 220° | 50K | ✓ |

NOTE: Use order code when ordering.

✓ DesignLights Consortium® Qualified

watch > like > follow

