



|                      |                              |
|----------------------|------------------------------|
| <b>Description</b>   | 18W 120V 2700K Spiral Shaped |
| <b>Ordering Code</b> | 00034                        |
| <b>UNSPSC Code</b>   | 39101619                     |

## Specifications

|                                     |                                                                                       |
|-------------------------------------|---------------------------------------------------------------------------------------|
| <b>Voltage Rating</b>               | 120                                                                                   |
| <b>Watts</b>                        | 18                                                                                    |
| <b>mA</b>                           | 290                                                                                   |
| <b>Lumens per Watt</b>              | 66                                                                                    |
| <b>Base Type</b>                    | Medium Screw (E26)                                                                    |
| <b>Bulb Type</b>                    | T2                                                                                    |
| <b>MOL in/mm</b>                    | 4.53/115                                                                              |
| <b>MOD in/mm</b>                    | 2.13/54                                                                               |
| <b>Mercury Content (mg)</b>         | 1.6                                                                                   |
| <b>HG Form</b>                      | amalgam                                                                               |
| <b>Approx Initial Lumens</b>        | 1200                                                                                  |
| <b>Approx Mean Lumens</b>           | 1200                                                                                  |
| <b>CT deg K</b>                     | 2700                                                                                  |
| <b>CRI</b>                          | 80                                                                                    |
| <b>Rated Life</b>                   | 10,000                                                                                |
| <b>Special Desc</b>                 | Not for use with dimmers, electronic timers, photocells, or motion/occupancy sensors. |
| <b>Equivalent</b>                   | 75W Incandescent                                                                      |
| <b>Ambient Operating Temp Range</b> | -18° C (0° F) to 50° C (122° F)                                                       |
| <b>Approvals</b>                    | cULus, IMERC, TCLP Compliant                                                          |

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335