


PARABOLIC FLUORESCENT SERIES

T8/T5 - 1' X 4' FLUORESCENT RECESSED PARABOLIC WITH 3" DEEP LOUVERS (SPECIFICATION GRADE)



APPLICATION:

Due to their high efficiency and glare control, Oracle Parabolic fixtures are the perfect choice for educational institutions, health care facilities, department stores and any other retail application.

PRODUCT FEATURES:

- Black inside reveal provides floating louvers appearance
- Housing and door frame interface provides a superior mechanical light seal and hinges down for easy lamp replacement
- Ballast can be accessed from below the ceiling
- Louvers are manufactured from rigid high-performance anodized aluminium and are fitted with cam latches and T-hinge to housing
- Post-painted high-gloss white powder coat finish maximizes distribution and efficiency while providing visual comfort
- All sides and corners are turned in and hemmed, removing sharp edges for safe handling and installation
- Four corner tie points are standard for safety wire support when required
- Built-in earthquake clips standard
- Same-day shipping on most options (Consult factory)
- Supplied standard with Philips Advance, GE or Universal ballast
- Wide variety of dimming and daylight harvesting options available
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)
- NEC required ballast disconnect is standard

LISTING

UL/C-UL listed to US and Canadian standard

WARRANTY

Guaranteed for one year against mechanical defects

Ordering Information > Example: 14-OP-2-32-T8-6-LD-ADV-10-MVOLT

14	OP									
FIXTURE SIZE	SERIES	TRIM TYPE	VOLTAGE ¹	# OF BALLAST	BALLAST FACTOR	LAMP INSTALLED				
14-1' X 4'	OP-Oracle Parabolic Troffer	(Blank)-Grid (Consult factory for Slot T mounting option)	(Blank) - MVOLT (120/277) 120 277 347	(Blank) - 1 Ballast 2 - 2 Ballasts	(Blank)- Normal BF HBF- High BF LBF- Low BF	(Blank)- No lamp L30K- 3000K L35K- 3500K L41K- 4100K L50K- 5000K				
# OF LAMPS/LAMP TYPE										
T8-LAMP 6 CELL 1-32-T8 (1 lamp/32W/T8) 6 CELL 2-32-T8 (2 lamps/32W/T8)		T5 LAMP 6 CELL 1-28-T5 (1 lamp/28W/T5) 1-54-T5HO (1 lamp/54W/T5HO) 6 CELL 2-28-T5 (2 lamps/28W/T5) 2-54-T5HO (2 lamps/54W/T5HO)								
(For other lamp type, please consult factory)										
BALLAST CONFIGURATION & CODE										
32W/T8	28W/T5	54W/T5HO	DESCRIPTION							
(Blank)	-	-	Electronic Instant Start							
EPS	(Blank)	(Blank)	Electronic Program Start							
ADV-7	-	ADV-7	Advance Mark-7 ¹							
ADV-10	-	ADV-10	Advance Mark-10 ¹							
-	ADV-OPT	-	Advance Optanium ¹							
ADV-ESS	-	-	Advance Essential ¹							
ADV-ROVR	-	ADV-ROVR	Advance Rover ¹							
LUT-EHD	LUT-EHD	LUT-EHD	Lutron Ecosystem H-Series ¹							
LUT-2W	-	-	Lutron Tu-Wire ¹							
LUT-EC5	LUT-EC5	-	Lutron Ecosystem ¹							
LUT-EC3	LUT-EC3	LUT-EC3	Lutron Eco-10 ¹							
LUT-TVE	-	-	Lutron Tve ¹							
LUT-H3D	LUT-H3D	LUT-H3D	Lutron Hi-Lume 3D ¹							
-	-	LUT-ECD	Lutron Ecosystem (347V Only) ¹							
1- Voltage must be specified for dimming ballast.										
EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)										
ORDER CODE		DESCRIPTION								
EMG-T8-BX-450		Up to 450 L. for T8 or BX								
EMG-T8-BX-600		Up to 600 L. for T8 or BX								
EMG-T8-BX-700		Up to 700 L. for T8 or BX								
EMG-T8-BX-1400		Up to 1400 L. for T8 or BX								
EMG-T5-520		Up to 520 L. for T5								
EMG-T5-T5HO-700		Up to 700 L. for T5 or T5HO								
EMG-T5-T5HO-1300		Up to 1300 L. for T5 or T5HO								
EMG-T8-BX-T5-T5HO-3200		Up to 3200 L. for T8, BX, T5 or T5HO								
EMG-SD-T8-BX-T5-T5HO-1400		Self-Diagnostic 1400 L. for T8, BX, T5 or T5HO								
EMG-ICE-T8-BX-T5-T5HO-1400		ICE Pack 1400 L. for T8, BX, T5 or T5HO								
GTD		Generator Transfer Device								
MANY OTHER BODINE AND IOTA EMERGENCY PACKS ARE AVAILABLE. PLEASE CONSULT FACTORY. VISIT WWW.BODINE.COM OR WWW.IOTAENGINEERING.COM FOR MORE DETAILS.										
OTHER OPTIONS										
14FK		- Flange Kit for 1' X 4' Fixture				SBF		- Internal Slow-Blow Fuse		
C3		- 6' 3-wire Flex Cable (Single Circuit)				RIS		- Radio Interference Suppressor		
C4		- 6' 4-wire Flex Cable (Double Circuit)				USA		- Made in America Compliance		
FBF		- Internal Fast Blow Fuse				Special options are available				

1- Voltage must be specified for dimming ballast.

T5/T8
1'X4'
OP

Fluorescent Recessed Parabolic