



APPLICATION:

Due to their high efficiency and glare control, Oracle Parabolic fixtures are the perfect choice for educational institutions, health care facilities, department stores and any other retail application.

PRODUCT FEATURES:

- Black interior reveal provides floating louvers appearance
- Housing and door frame interface provide a superior mechanical light seal and hinges down for easy lamp replacement
- Louvers are manufactured from rigid high-performance anodized aluminium and are fitted with cam latches and T-hinge to housing
- Post-painted high-gloss white powder coat finish maximizes distribution and efficiency while providing visual comfort
- All sides and corners are turned in and hemmed, to remove sharp edges for safe handling and installation
- Designed for seamless and hassle-free surface mounted installations
- Same-day shipping on most options (Consult factory)
- Supplied standard with Philips Advance, GE or Universal ballast
- Wide variety of dimming and daylight harvesting options available
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)
- NEC required ballast disconnect is standard

LISTING

UL/C-UL listed to US and Canadian standards

WARRANTY

Guaranteed for one year against mechanical defects

T5/T8
2' X 4'
OSMP

Fluorescent Surface Mount Parabolic

Ordering Information > Example: 14-OSMP-2-32-T8-6-LD-ADV-10-MVOLT

14	OSMP								
FIXTURE SIZE 14-1' X 4'	SERIES OSMP- Oracle Surface Mount Parabolic		VOLTAGE¹ (Blank) - MVOLT (120/277) 120 277 347	# OF BALLAST (Blank) - 1 Ballast 2 - 2 Ballasts	BALLAST FACTOR (Blank) - Normal BF HBF - High BF LBF - Low BF		LAMP INSTALLED (Blank) - No lamp L30K - 3000K L35K - 3500K L41K - 4100K L50K - 5000K		
# OF LAMPS/LAMP TYPE							FINISH LD-Diffuse Silver		
T8-LAMP 6 CELL 1-32-T8 (1 lamp/32W/T8) 6 CELL 2-32-T8 (2 lamps/32W/T8)		T5 LAMP 6 CELL 1-28-T5 (1 lamp/28W/T5) 1-54-T5HO (1 lamp/54W/T5HO) 6 CELL 2-28-T5 (2 lamps/28W/T5) 2-54-T5HO (2 lamps/54W/T5HO)					# CELLS 6- (1X6) 1, 2 Lamp		
<i>(For other lamp type, please consult factory)</i>									
BALLAST CONFIGURATION & CODE									
32W/T8	28W/T5	54W/T5HO	DESCRIPTION						
(Blank)	-	-	Electronic Instant Start						
EPS	(Blank)	(Blank)	Electronic Program Start						
ADV-7	-	ADV-7	Advance Mark-7 ¹						
ADV-10	-	ADV-10	Advance Mark-10 ¹						
-	ADV-OPT	-	Advance Optanium ¹						
ADV-ESS	-	-	Advance Essential ¹						
ADV-ROVR	-	ADV-ROVR	Advance Rover ¹						
LUT-EHD	LUT-EHD	LUT-EHD	Lutron Ecosystem H-Series ¹						
LUT-2W	-	-	Lutron Tu-Wire ¹						
LUT-EC5	LUT-EC5	-	Lutron Ecosystem ¹						
LUT-EC3	LUT-EC3	LUT-EC3	Lutron Eco-10 ¹						
LUT-TVE	-	-	Lutron Tve ¹						
LUT-H3D	LUT-H3D	LUT-H3D	Lutron Hi-Lume 3D ¹						
-	-	LUT-ECD	Lutron Ecosystem (347V Only) ¹						
EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)									
ORDER CODE	DESCRIPTION								
EMG-T8-BX-450	Up to 450 L. for T8 or BX								
EMG-T8-BX-600	Up to 600 L. for T8 or BX								
EMG-T8-BX-700	Up to 700 L. for T8 or BX								
EMG-T8-BX-1400	Up to 1400 L. for T8 or BX								
EMG-T5-520	Up to 520 L. for T5								
EMG-T5-T5HO-700	Up to 700 L. for T5 or T5HO								
EMG-T5-T5HO-1300	Up to 1300 L. for T5 or T5HO								
EMG-SD-T8-BX-T5-T5HO-1400	Self-Diagnostic 1400 L. for T8 , BX , T5 or T5HO								
EMG-ICE-T8-BX-T5-T5HO-1400	ICE Pack 1400 L. for T8 , BX , T5 or T5HO								
GTD	Generator Transfer Device								
MANY OTHER BODINE AND IOTA EMERGENCY PACKS ARE AVAILABLE, PLEASE CONSULT FACTORY. VISIT WWW.BODINE.COM OR WWW.IOTAENGINEERING.COM FOR MORE DETAILS.									
OTHER OPTIONS									
FBF - Internal Fast Blow Fuse					SBF - Internal Slow-Blow Fuse				
C3 - 6' 3-wire Flex Cable (Single Circuit)					RIS - Radio Interference Suppressor				
C4 - 6' 4-wire Flex Cable (Double Circuit)					USA - Made in America Compliance				
Special options are available									

¹ - Voltage must be specified for dimming ballast.