


T8/T5 - 2' X 2' FLUORESCENT RECESSED VOLUMETRIC
(CENTER MOUNT RADIAL "HT" LENS)



APPLICATION:

Ideal for any application which requires high-efficiency lighting with minimum energy consumption such as educational institutions, office spaces, health care facilities, office complexes and retail stores.

EFFICIENT SOLUTION:

EFFICIENT SOLUTION: High reflectance optical engine delivers main beam focus through the revolutionary radial High Transmission (HT) acrylic diffusing panel with low brightness glow. With 95% transmission and 89% haze, the result is extraordinary control and efficiency.

OPTICAL SYSTEM: A+ Rated high-gloss white powder coat paint provides maximum distribution and visual comfort.

PRODUCT FEATURES:

- Dawn Series proprietary "light lock system" prevents light leakage at both ends of lamp shields
 - Door frame hinges for easy installation of lamps and hassle-free maintenance
 - Ballast can be accessed from below the ceiling
 - All sides and corners are turned in and hemmed, removing sharp edges for safe handling and installation, built-in earthquake clips
 - Construction of lamp shields conceals lamps and ballast access cover
 - Supplied standard with Philips Advance, GE or Universal ballast
 - Wide variety of dimming and daylight harvesting options available
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)
 - NEC required ballast disconnect is standard
- LISTING**
UL/C-UL listed to US and Canadian standard
- WARRANTY**
Guaranteed for one year against mechanical defects

LISTING

UL/C-UL listed to US and Canadian standard

WARRANTY

Guaranteed for one year against mechanical defects

Ordering Information > Example: 22-OD2V-2-17-T8-ADV-10-MVOLT

22

OD2V

FIXTURE SIZE

22-2' X 2'

TRIM TYPE

(Blank)- Grid (Consult factory for Slot T mounting option)

SERIES

OD2V-Oracle Dawn
Direct/Indirect

OF LAMPS/LAMP TYPE

1-17-T8 (1 lamp/17W/T8)

2-17-T8 (2 lamps/17W/T8)

3-17-T8 (3 lamps/17W/T8)

1-14-T5 (1 lamp/14W/T5)

2-14-T5 (2 lamps/14W/T5)

3-14-T5 (3 lamps/14W/T5)

1-24-T5H0 (1 lamp/24W/T5H0)

2-24-T5H0 (2 lamps/24W/T5H0)

3-24-T5H0 (3 lamps/24W/T5H0)

1-40-BX (1 lamp/40W/BX TT)

2-40-BX (2 lamps/40W/BX TT)

3-40-BX (3 lamps/40W/BX TT)

(For other lamp type, please consult factory)

VOLTAGE¹

(Blank)- MVOLT (120/277)
120
277
347

OF BALLAST

(Blank) - 1 Ballast
2 - 2 Ballasts

*MASTER/SATELLITE

MAS1-Master fixture w/ 1 ballast & 11 ft. flex
MAS2-Master fixture w/ 2 ballast & 11 ft. flex
SAT-Satellite fixture w/o ballast
**must be ordered separately*
EX: 22-OD2V-2-17-T8-MAS2
and 22-OD2V-2-17-T8-SAT
**Available only with 2 or 3 lamps T8 only. Dimming option is not available when ordering Master/Satellite.*

BALLAST FACTOR

(Blank)- Normal BF
HBF- High BF
LBF- Low BF

LAMP INSTALLED

(Blank)- No lamp
L30K- 3000K
L35K- 3500K
L41K- 4100K
L50K- 5000K

BALLAST CONFIGURATION & CODE

17W/T8	14W/T5	24W/T5H0	40W/BX	DESCRIPTION
(Blank)	-	-	(Blank)	Electronic Instant Start
EPS	(Blank)	(Blank)	EPS	Electronic Program Start
ADV-7	-	-	-	Advance Mark-7 ¹
ADV-10	-	ADV-10	ADV-10	Advance Mark-10 ¹
-	-	-	-	Advance Optanium ¹
ADV-ESS	-	-	-	Advance Essential ¹
ADV-ROVR ¹	-	-	-	Advance Rover ¹
-	-	-	-	Lutron Ecosystem H-Series ¹
-	-	-	-	Lutron Tu-Wire ¹
LUT-EC5 ¹	LUT-EC5 ¹	LUT-EC5	LUT-EC5	Lutron Ecosystem ¹
LUT-EC3	LUT-EC3 ¹	LUT-EC3	LUT-EC3	Lutron Eco-10 ¹
-	-	-	-	Lutron Tve ¹
LUT-H3D	LUT-H3D ¹	LUT-H3D	LUT-H3D	Lutron Hi-Lume 3D ¹
-	-	-	-	Lutron Ecosystem (347V Only) ¹

1- Voltage must be specified for dimming ballast.

EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)

ORDER CODE	DESCRIPTION
EMG-T8-BX-450	Up to 450 L. for T8 or BX
EMG-T8-BX-600	Up to 600 L. for T8 or BX
EMG-T8-BX-700	Up to 700 L. for T8 or BX
EMG-T8-BX-1400	Up to 1400 L. for T8 or BX
EMG-T5-520	Up to 520 L. for T5
EMG-T5-T5H0-700	Up to 700 L. for T5 or T5H0
EMG-T5-T5H0-1300	Up to 1300 L. for T5 or T5H0
EMG-T8-BX-T5-T5H0-3200	Up to 3200 L. for T8, BX, T5 or T5H0
EMG-SD-T8-BX-T5-T5H0-1400	Self-Diagnostic 1400 L. for T8, BX, T5 or T5H0
EMG-ICE-T8-BX-T5-T5H0-1400	ICE Pack 1400 L. for T8, BX, T5 or T5H0
GTD	Generator Transfer Device

MANY OTHER BODINE AND IOTA EMERGENCY PACKS ARE AVAILABLE, PLEASE CONSULT FACTORY. VISIT WWW.BODINE.COM OR WWW.IOTAENGINEERING.COM FOR MORE DETAILS.

OTHER OPTIONS

22FK	- Flange Kit for 2' X 2' Fixture	SBF	- Internal Slow-Blow Fuse
C3	- 6' 3-wire Flex Cable (Single Circuit)	RIS	- Radio Interference Suppressor
C4	- 6' 4-wire Flex Cable (Double Circuit)	USA	- Made in America Compliance
FBF	- Internal Fast Blow Fuse		