



APPLICATION:

Ideal for general office lighting, corridors, educational institutions, hospitals, and retail.

PRODUCT FEATURES:

- Heavy-duty 20-gauge steel utilized throughout for durability and code compliance
- Provides even illumination up to 180 degrees
- Pretreated with five-stage iron phosphate process to ensure superior paint adhesion
- · Painted high-gloss baked white enamel
- Shallow design is ideal for commercial, industrial and residential spaces requiring general
- Suitable for dry and damp environments
- Thermally protected, self-resetting, Class P, NPF, non-PCB and UL listed ballast
- Lightweight design enables for quick, easy installation
- Not intended for continuous row mounting
- · NEC required ballast disconnect is standard
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)

LENS - Prismatic acrylic Lens

LISTING

UL/C-UL listed to US and Canadian standards

Guaranteed for one year against mechanical defects

T8 **0EW**





FIXTURE SIZE

4

SERIES **OEW**-Oracle

OEW

Economy Wrap Around

WATTAGE

4' FIXTURE 2-32-T8 (2 lamps/32W/T8)

2-17-T8 (2 lamps/17W/T8) 4-32-T8 (4-lamps/32W/T8)

Ordering Information > Example: 4-OEW-4-32-T8-ADV-10-MVOLT-EMG-T8-BX-700

VOLTAGE # OF BALLAST BALLAST FACTOR **120**- 120 (Blank) - 1 Ballast (Blank) - Normal BF 2- 2 Ballasts

EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)			
ORDER CODE	DESCRIPTION		
EMG-T8-BX-450	Up to 450 L. for T8 or BX		
EMG-T8-BX-600	Up to 600 L. for T8 or BX		
EMG-T8-BX-700	Up to 700 L. for T8 or BX		
EMG-T8-BX-1400	Up to 1400 L. for T8 or BX		
EMG-SD-T8-BX-T5-T5H0-1400	Self-Diagnostic 1400 L. for T8, BX, T5 or T5H0		
EMG-ICE-T8-BX-T5-T5H0-1400	ICE Pack 1400 L. for T8, BX, T5 or T5H0		
GTD	Generator Transfer Device		

BALLAST CONFIGURATION & CODE			
17W/T8	32W/T8	DESCRIPTION	
(Blank)	(Blank)	Electronic Program Start	

OTHER OPTIONS OCMS - Motion Sensor - Made in America Compliance