



**90+**  
CRI

PROUDLY  
ASSEMBLED in  
AMERICA

**SAMEDAY**  
SHIPPING

#### PRODUCT FEATURES:

- Manufactured in heavy-gauge steel for durability and code compliance
- Pretreated with five-stage iron phosphate process to ensure superior paint adhesion
- Painted high-gloss baked white enamel
- Shallow design is ideal for commercial, industrial and residential spaces requiring general illumination
- Suitable for dry and damp environments
- Lightweight design enables for quick, easy installation

**LENS** - White acrylic diffuse lens

#### WARRANTY

Limited 5 Year Warranty

**OPTICS** - The OSC-LED uses a frosted acrylic lens to scatter the light emitted from the LED chips into functional light. The LED offered in the OSC-LED has the highest return on initial investment compared to other standard lighting solutions.

**PERFORMANCE** - The light engines found in the OSC are rated at 90+ CRI and are available in multiple CCTs: 3000K, 3500K and 4000K. Rated and tested to LM-79 and LM-80 standards. The LEDs are also binned to a 3-step MacAdam ellipses to achieve consistent color from fixture to fixture.

**ELECTRICAL** - Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120 or 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

**QUALITY CONTROL** - Every fixture is turned on and rigorously tested by our QC Department before shipping.

**INSTALLATION** - Fixture easily mounts directly over a 4" recessed outlet box, and most standard size junction boxes.

**WARRANTY** - Limited 5 Year Warranty

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C. Specifications are subject to change without notice.

#### Ordering Information > Example: 4-OSC-LED-5000L-DIM10-MVOLT-40K-O-EMG-LED

FIXTURE SIZE	SERIES	TYPE	SERIES	DIMMING	VOLTAGE	CCT	CRI	EMERGENCY OPTION
4 - 4'	OSC-Oracle Cloud	LED	4000L (4000 Lumens) 5000L (5000 Lumens)	DIM10	MVOLT 120 277	30K - 3000K 35K - 3500K 40K - 4000K	90+	O-EMG-LED