

ELM-600

Emergency Recessed Light

Architectural

Catalog Number:

Project Name:

Type:

Note:

MAXILUME
ARCHITECTURAL LIGHTING



FEATURES

This recessed fixture is an excellent choice when an attractive recessed emergency light is required. In cases of AC power loss, it provides a minimum of 90 minutes illumination. A trouble-free lead-calcium battery is provided with the fixture. The lamp head may be adjusted through the full range of motion because of the special swivel-track design.

HOUSING

- Die-formed all aluminum construction for maximum heat dissipation and rust protection. Adjusts vertically in plaster frame for 1/2" to 1-3/8" ceiling.
- Wire through junction box.
- Preinstalled adjustable bar hanger.

FACE

- UV-stabilization prevents discoloration of the product.
- The thermoplastic trim of the product makes it corrosion-proof and scratch-and impact-resistant.
- Beveled injection molded face with one round lamp head molded into sloped side surfaces of fixture.

ELECTRICAL

- 120V or 277V input
- Reset is automatic
- Hassle-free wiring without the need for additional hardware

LAMPS

- Beveled face with (2) 5 Watt MR16 lamp heads

BATTERY

- Indicator light shows high charge and readiness for operation
- 6V, 4 amp-hour sealed-lead acid battery works during power failures
- Replaceable and requires no maintenance
- When completely charged, supplies emergency power for 90 minutes.

TESTING

- Test Button
- Solid state line latched low voltage disconnect to avoid deep discharge
- Safeguarded against short circuits
- Power is automatically interrupted in cases of brown-out

LISTED

- Damp location approved

