



Super-Brite Flexilight

5/8"
DIAMETER


The Super-Brite rope light, 5/8" in diameter, is made with super-bright bulbs (6V/100MA). Each bulb emits 66.7% higher brightness than the standard miniature bulb. Since we only use the highest-quality PVC material along with UV additives, the Super-Brite Flexilight can be used in indoor or outdoor applications and can withstand both freezing and scorching weather.

Superior brightness makes these rope lights perfect for creating highlights in decorations. Due to its larger bulbs and thickness, Super-Brite is also designed for large-scale decorations, such as those on a skyscraper, across a bridge, or on a large billboard.

Number of wire	2
Number of bulb/foot	12
Diameter	5/8"
Shape	Round
Colors available (PVC)	Clear:
	Clear, Red, Yellow, Blue,
	Green, Orange, Purple
	Fluorescent Colors:
	Green, Orange and Pink
	Pearl Colors:
	White, Red, Yellow, Blue & Green

FLEXIBLE ROPELIGHT

Specifications of Super-Brite Flexilight:

Structure	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
	110-120V	100'	20"	6.5V 0.07A 0.46W	12	8.0W/foot

Packages Available

Item Number	Length	Package	ERI U	- 120	- 150	- COLOR
			Item No.	Voltage	Length	Specify color


ERI U-120-150

150'

/Roll

(Available in 150' Rolls only, no custom cut)


NOTE: EACH ROLL INCLUDES; 3pcs ERIU-1 Power Cords, 3pcs IU3 Splice Connectors, 3pcs IU4 End Caps



Super-Brite Flexilight Accessories:

ERIU-1	120V Super-Brite Flexilight 6ft. Power Cord w/ Power Connector
IU3	Super-Brite Flexilight Splice Connector
IU4	Super-Brite Flexilight End Caps
F5	Super-Brite Flexilight Tie Strap
IU6	Super-Brite Flexilight Mounting Clips
F7	Super-Brite Flexilight Suction Cup
IU8	Super-Brite Flexilight 6ft. Channel
IU9	Super-Brite Flexilight Easy Splice Connector
IU10	Super-Brite Flexilight Y-cord
IU14	Housing Clamp for Splice Connector
IU103	Super-Brite Flexilight PVC Connector
IU22	Super-Brite Flexilight PVC T-Connector
IU23	Super-Brite Flexilight PVC X-Connector

ERI U



FLEXIBLE ROPELIGHT

Standard Controller

MODEL	VOLTAGE AVAILABLE	MAX. LENGTH	FUNCTIONS
ERWL-2C-ERI U-110	120V	150 FT.	Static/Flashing Gradual Color-Change

