


OPR2-LED

UP TO
4000
LUMENS



DIMENSIONS:



Catalog Number:

Project Name:

Note:

Type:

ORACLE
LIGHTING

APPLICATION - OPR2-LED pendants offer direct ambient illumination. Its clean, classic look provides light over any environment including schools, boardrooms, office areas, hotels, lobbies, restaurants, etc. OPR2-LED is suitable for any design application with its variety in sizes.

CONSTRUCTION - Rigid aluminum design ensures longevity and endurance. A high quality, high transmission, glare free lens offers smooth illumination.

PERFORMANCE - The honeycomb light engines found in the OPR2-LED are rated at 80+ CRI and are available in multiple CCTs: 3000K, 3500K and 4000K. Rated and tested to LM-79 and LM-80 standards. The LEDs are also binned to a 3-step MacAdam ellipse to achieve consistent color from fixture to fixture.

ELECTRICAL - Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

DIMMING - The OPR2-LED comes standard with 0-10V dimming on either 120, in and 277V. 347V please consult factory. Dimmable down to 1% of initial lumens. Also available in Lutron dimming options. Consult factory for dimmer compatibility.

MOUNTING - Comes standard in ceiling mount or adjustable cable suspension system providing fast installation into a variety of interior heights, including sloped ceilings. Consult factory for additional mounting options.

QUALITY CONTROL - Every fixture is rigorously tested by our QC Department before shipping.

WARRANTY - Limited 5 Year Warranty

EXAMPLE: OPR2-LED-1-2000L-DIM10-MVOLT-40K-WH-CM

SERIES	CCT	LUMENS	DIMMING/VOLTAGE	EMERGENCY	COLOR	MOUNTING OPTION
OPR2-LED	☐ 30K ☐ 35K ☐ 40K	☐ 4000L	☐ DIM10-MVOLT ☐ LUTH-MVOLT ☐ DIMTR-120	☐ EMG-LED Remote Mounted for Surface Mount	☐ WH (Matt White) ☐ BK (Black) ☐ SI (Silver) Custom color available, please consult factory. Must provide RAL#	☐ CM-Ceiling Mount ☐ SM-10' Suspended Mount (Consult factory for other sizes)
	☐ TWH-50K-27K ☐ TWH-LTX-80K-16K ☐ TWH-WBL3-65K-27K	☐ 4000L	☐ DIM10-MVOLT ☐ DMX-512-MVOLT ☐ DMX-RDM-MVOLT ☐ DLM (WBL3 Only)			
	☐ WDM	☐ 4000L	☐ DIM10-MVOLT ☐ DMX-512-MVOLT ☐ DMX-RDM-MVOLT ☐ DALI-MVOLT			
	☐ RGBW	☐ 4000L	☐ DMX-512-MVOLT			