ORBIT-LED



Catalog Number: Project Name: Type:

> 1226 12 WATT

APPLICATION - Orbit is a clean and modern form that adds a great circular glow to a space. Orbit's smooth lines can fit into a wide range of decorative styles. It can be used in lobbies, restaurants, office spaces and educational facilities. Orbit's rare form can either stand out or blend into various lighting applications.

CONSTRUCTION - Rigid aluminum design ensures longevity and endurance plus a high quality, high transmission, glare free lens for smooth illumination.

PERFORMANCE - The honeycomb light engines found in the Orbit is rated at 80+ CRI and are available in multiple CCTs: 3000K, 3500K and 4000K. Rated and tested to LM-79 and LM-80 standards. The LEDs are also binned to a 3-step MacAdam ellipse to achieve consistent color from fixture to fixture.

ELECTRICAL - Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

DIMMING - The ORBIT-LED comes standard with 0-10V dimming on either in 120 and 277V. 347V please consult factory. Dimmable down to 1% of initial lumens. Also available in Lutron dimming options. Consult factory for dimmer compatibility.


MOUNTING - Comes standard in adjustable cable suspension system providing fast installation into a variety of interior heights, including sloped ceilings. Consult factory for additional mounting options.

QUALITY CONTROL - Every fixture is rigorously tested by our QC Department before shipping.

WARRANTY - Limited 5 Year Warranty

Note:

DIMENSIONS:



EXAMPLE: ORBIT-LED-2-1000L-DIM10-MVOLT-40K-WH-CM						
SERIES	SIZE	LUMENS - DIMMING	CCT	EMERGENCY	COLOR	MOUNTING OPTION
ORBIT-LED	2' (1.8')	□ 1000L-DIM10-MV0LT □ 1000L-LUTH-MV0LT □ 1000L-DIMTR-120	□ 30K □ 35K □ 40K	Remote Mounted for Surface Mount	Custom color available, please consult factory. Must provide RAL#	□ SM-10' Suspended Mount (Consult factory for other sizes)

