

DECORATOR SELF-GROUNDING TAMPER-RESISTANT HALF CONTROLLED RECEPTACLE

MODEL NO: 63200-TR-PLH



DESCRIPTION

The ENERLITES 62080-TR-PLH is a receptacle with “controlled” marked on one of the two outlets. The controlled outlet is intended to be powered by an external sensor or switch. Tamper-resistant shutters prevent insertion of foreign objects. Back wired with break-off tabs for easy two-circuit conversion. All duplex receptacles are designed with thermoplastic construction and feature a shallow build for maximum wiring room.

FEATURES

- Optional grounding with self-grounding clip or green terminal screw
- Break-off tabs for easy two-circuit conversion
- Push-in #14 AWG Cu solid wire for 15A branch circuit only
- Removable yoke tabs for ideal alignment
- Terminal screws backed out ready for wiring
- Combination Slot/Phillips head mounting and terminal screws ease installation
- Heavy-duty impact resistant thermoplastic construction for long service life in commercial applications
- Back wiring terminals accept both solid and stranded wire to ease installation

SPECIFICATIONS

Amperage	20 Amp
Voltage	125 VAC
NEMA	5-20R
Termination	Back Wiring
Material	Thermoplastic
Operating Temperature	-104° F to 167° F
Warranty	2 Years

TESTING & CODE COMPLIANCE



APPLICATIONS

- Homes
- Apartments
- Condominiums
- Offices
- Hotels
- Restaurants

SPECIFICATION SUBMITTAL

Job Name	<input type="text"/>	Job Number	<input type="text"/>
Notes	<input type="text"/>		