


PRODUCT CODE: DLSGS3-813WD-WH
3 INCH LED SLIM GIMBAL DOWN LIGHT


PRODUCT DESCRIPTION

The Etlin-Daniels DLSGS3-813WD-WH LED 3 inch Slim Gimbal Recessed Downlight offers a modern, energy-efficient solution for retrofitting existing incandescent & halogen recessed fixtures, as well as for new construction. Requiring only a 2-3/4" round hole, and with the driver inside a compact connection box (does not require an external j-box) the DLSG series is simple to install and is both IC rated and Airtight. The 38° beam with 30° tilt and 360° rotation is perfect for sloped ceilings or to highlight artwork. Triac dimmer compatible with Warm Dim feature - 3000K dims down to 2200K // 4000K dims down to 3000K. Available in round and square face in white, brushed nickel and black trim. 6W version supplies 420lm (FMW equivalent) and 8W version supplies 600lm (EXN compatible).

FEATURES


- LED Indoor Light Source.
- 3" Gimbal Recessed Downlight.
- Durable die-cast aluminum alloy for optimal heat dissipation.
- Scratch resistant, smooth finish.
- Unique gimbal design with 30° tilt and 360° rotation.
- Type IC and Airtight, Damp location rated.
- Ceiling clearance required: 2-1/2" for Romex, 3-1/2" for MC or BX installations.
- Triac Warm Dim down to 10%.
- Warm Dim - 3000K dims to 2200K // 4000K dims to 3000K.
- Guaranteed 98% Lumen Maintenance after 6,000 hour life.
- Round and square housings available in white, black and brushed nickel.
- 5 year warranty
- L70 - 50,000 hours
- Energy Star certified.

PRODUCT SPECIFICATIONS (OPTICAL DATA)

PRODUCT SPECIFICATIONS (ELECTRICAL DATA)

LED TYPE	LED QTY	SYSTEM EFFICACY	LUMENS	COLOR TEMPERATURE	BEAM ANGLE	CRI	SYSTEM EFFICIENCY	VOLTAGE	POWER FREQ.	POWER FACTOR
COB	1 CHIPS	75LM/W	600LM	3000K-2200K	38°	>80CRI	>82%	AC120V	50-60HZ	>0.90


PRODUCT SPECIFICATIONS


WATTAGE	FIXTURE MATERIAL	LIFE SPAN	STORAGE TEMP	OPERATING TEMP	PRODUCT DIMENSIONS	CARTON SIZE	
8W	ACRYLIC LENS/ ALUMINUM BODY	>50,000 HOURS	-20°C~+40°C -4°F~+104°F	-20°C~+40°C -4°F~+104°F	3.31 X 3.31 X 1.73 INCHES (84 X 84 X 44 MM)	14.76 X 9.25 X 12.20 INCHES (375 X 235 X 310MM)	

ADDITIONAL INFORMATION

INSTALLATION METHOD
RECESSED CEILING MOUNT
FIXTURE COLOR
WHITE
CONTROL TYPE
WARM DIM TRIAC

PRODUCT CODE: DLGS3-813WD-WH
3 INCH LED SLIM GIMBAL DOWN LIGHT
LUMINAIRE PHOTOMETRIC (TEST REPORT)
ILLUMINANCE (AT A DISTANCE) FLUX OUT: 322.9LM

3.28FT 1M	43.91,67.92FC 472.7,731.1LX		2.99FT 91.12CM
6.56FT 2M	10.98,16.98FC 118.2,182.8LX		5.979FT 182.24CM
9.84FT 3M	4.879,7.547FC 52.52,81.23LX		8.969FT 273.36CM
13.12FT 4M	2.745,4.245FC 29.54, 45.69LX		11.96FT 364.49CM
16.4FT 5M	1.757, 2.717FC 18.91, 29.24LX		14.95FT 455.61CM
HT	EAVG/EMAX	ANGLE: 48.9DEG	DIA

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

CERTIFICATIONS
DRIVER/LED CHIP
120V APPROVED DIMMERS
ACCESSORIES


LUTRON: CTCL153PDH · CTCL153P
CT-600P · DVCL153P
LEVITON: 6672 · 6674
COOPER: HCL453PTCCCV6



ROUGH-IN PLATE
PART# DLGR3-RIP3



72" EXTENSION CORD
PART# DLGR3-EC72



240" EXTENSION CORD
PART# DLGR3-EC240

ORDERING INFORMATION - DLGS SERIES

SERIES	SHAPE	SIZE	WATTAGE	VOLTAGE	COLOR TEMPERATURE	DIMMABLE	COLOUR
E.G. DLSG	S	3	8	1	3	WD	WH
DLSG - DOWN LIGHT	S - SQUARE	3"	8 - 8W	1 - 120V	3 - 3000K-2200K	WD - WARM DIM	WH - WHITE
SLIM GIMBAL							BL - BLACK
							BN - BRUSHED NICKEL

Head Office - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · Tel: 416.741.7336 · Fax: 416.741.9104

Toll Free: in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)

www.etlin-daniels.com · For sales/service questions · sales@etlin.com