


PRODUCT CODE: STL54-35WL50-WH

4FT. LED LINEAR STRIP



PRODUCT DESCRIPTION

The new generation of Etlin-Daniels STL5 series LED Strip Fixtures offers the latest in performance and flexibility for both fixture replacement and upgrades, as well as for new construction. These fixtures can be surface mounted to walls and ceilings, or suspended with optional v-hooks and chain. The high efficacy of 130lm/w allows for superior energy savings and the frosted lens delivers even and glare-free illumination. End knockouts provide for continuous row mounting, and wire guards are available to protect against physical shock. An innovative and easy-to-install j-box cover comes with each fixture to ensure that wires are properly protected and the proper aesthetic is maintained.

The STL5 series comes with an innovative driver that allows for adding a cost-effective PIR sensor option to each fixture, with multiple dimming, daylight settings and on / off options. Available in 20W - 2 foot / 35W - 4 foot / 65W - 8 foot lengths in both 4000K & 5000K, 120-347V. If not using the PIR sensor option, you can add to the energy savings by taking advantage of the available 0-10V Continuous Dimming.

FEATURES

- LED Indoor Light Source
- Light weight powder coated metal housing with frosted glare free lens
- Fixtures can be surface or suspension mounted
- End knockouts for continuous mounting.
- 120-347V
- Damp location rated
- Optional bracket and PIR Sensor available - Remote Control required
- Each STL5-SENPIR can control up to a total of 4 fixtures - any length
- J-box covers included
- Wire guards available
- 0-10V Continuous Dimming
- 5 year warranty
- L70 - 50,000 hours
- DLC certified

PRODUCT SPECIFICATIONS (OPTICAL DATA)

| LED TYPE | LED QTY | SYSTEM EFFICACY | LUMENS | COLOUR TEMPERATURE | CRI | VOLTAGE | POWER FREQ. | POWER FACTOR | HARMONIC DISTORTION |
|----------|----------|-----------------|--------|--------------------|--------|-------------|-------------|--------------|---------------------|
| SEOUL | 84 CHIPS | 132LM/W | 4620LM | 5000K | >80CRI | AC120V-347V | 50-60HZ | >0.90 | <10% |

PRODUCT SPECIFICATIONS (ELECTRICAL DATA)

PRODUCT SPECIFICATIONS

| WATTAGE | FIXTURE MATERIAL | LIFE SPAN | STORAGE TEMP | OPERATING TEMP | PRODUCT DIMENSIONS | CARTON SIZE | |
|---------|--------------------|---------------|-----------------------------|----------------------------|--|--|---|
| 35W | STEEL/FROSTED LENS | >50,000 HOURS | -40°C~+85°C -40°F~+185°F | -20°C~+55°C 55°F~+131°F | 48 X 3.35 X 3.56 INCHES (1219.2 X 85.09 X 90.42 MM) | 48.82 X 3.74 X 3.94 INCHES (1240 X 95 X 100.1 MM) |  |

ADDITIONAL INFORMATION

INSTALLATION METHOD

SUSPENDED OR SURFACE

FIXTURE COLOUR

WHITE

CONTROL TYPE


0-10V DIMMABLE

PRODUCT CODE: STL54-35WL50-WH


4FT. LED LINEAR STRIP

LUMINAIRE PHOTOMETRIC (TEST REPORT)

| ILLUMINANCE (AT A DISTANCE) - | | VERT BEAM | HORIZ BEAM |
|-------------------------------|-------------|------------------|------------------|
| 2.29FT 0.7M | 2,938.95LUX | | |
| 4.26FT 1.3M | 734.74 LUX | 10.17FT 3.1M | 18.37FT 5.6M |
| 6.56FT 2.0M | 326.55 LUX | 15.42FT 4.7M | 27.56FT 8.4M |
| 8.85FT 2.7M | 183.68 LUX | 20.67FT 6.3M | 36.74FT 11.2M |
| 10.82FT 3.3M | 117.56 LUX | 25.92FT 7.9M | 45.93FT 14.0M |
| 13.12FT 4.0M | 81.64 LUX | 30.84 FT 9.4M | 55.12FT 16.8M |



| HT | EAVG/EMAX | VERT SPREAD: 99.5DEG HORI SPREAD: 129.0DEG | DIA |
|----|-----------|---|-----|
|----|-----------|---|-----|



CERTIFICATIONS



DRIVER/LED CHIP



MOUNTING OPTIONS/ACCESSORIES

| | | | | | | | |
|--|---|---|--|--|--|---|---|
|  SENSOR BRACKET - PART#: STL5-SENBK |  PIR SENSOR PART#: STL5-SEMPIR |  REMOTE CONTROL FOR SENPIR PART#: STL5-RC |  CHAIN - OPTIONAL PART#: STL-CH |  V HOOK - OPTIONAL PART#: STL-VHOOKS |  CONNECTOR BRACKET - PART#: STL5-CB |  WIRE GUARD - PART#: STL5-WG-4 |  LENS - PART#: STL54-LEN |
|--|---|---|--|--|--|---|---|

ORDERING INFORMATION - STL54 SERIES

| SERIES | SIZE | WATTAGE | VOLTAGE | LOW VOLTAGE | COLOR TEMPERATURE | DIMMABLE | FINISH |
|--------------------|--------|----------|--------------|----------------|-------------------|-----------|----------|
| E.G. STL5 | 4 | 35 | W | L | 5 | 0 | WH |
| STL5 - STRIP LIGHT | 4 - 4' | 35 - 35W | W - 120-347V | L - 12V OUTPUT | 5 - 5000K | 0 - 0-10V | WH-WHITE |

Head Office - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · Tel: 416.741.7336 · Fax: 416.741.9104

Toll Free: in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)

www.etlin-daniels.com · For sales/service questions - sales@etlin.com