



# SP13/41K-DIM



|                      |                                       |
|----------------------|---------------------------------------|
| <b>Description</b>   | 4100K 13W 120V Spiral Shaped Dimmable |
| <b>Ordering Code</b> | 06393                                 |
| <b>UNSPSC Code</b>   | 39101619                              |

## Specifications

|                                     |                                                                             |
|-------------------------------------|-----------------------------------------------------------------------------|
| <b>Voltage Rating</b>               | 120                                                                         |
| <b>Watts</b>                        | 13                                                                          |
| <b>Base Type</b>                    | Medium Screw (E26)                                                          |
| <b>MOL in/mm</b>                    | 4.92/125                                                                    |
| <b>MOD in/mm</b>                    | 2.28/58                                                                     |
| <b>Mercury Content (mg)</b>         | 2                                                                           |
| <b>HG Form</b>                      | amalgam                                                                     |
| <b>Approx Initial Lumens</b>        | 850                                                                         |
| <b>CT deg K</b>                     | 4100                                                                        |
| <b>CRI</b>                          | 80                                                                          |
| <b>Rated Life</b>                   | 8,000                                                                       |
| <b>Special Desc</b>                 | Dimmable down to 8%. Use only dimmers rated 600W or lower, made after 1995. |
| <b>Equivalent</b>                   | 60W Incandescent                                                            |
| <b>Ambient Operating Temp Range</b> | -18° C (0° F) to 40° C (104° F)                                             |
| <b>Approvals</b>                    | cULus, IMERC, TCLP Compliant                                                |

[watch](#) > [like](#) > [follow](#)



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335