



# SP85/41/MED



|                      |                                         |
|----------------------|-----------------------------------------|
| <b>Description</b>   | 4100K 85W 120V Spiral 4100K Medium Base |
| <b>Ordering Code</b> | 81183                                   |
| <b>UNSPSC Code</b>   | 39101619                                |

## Specifications

|                                     |                                                                                                                                                                                       |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Voltage Rating</b>               | 120                                                                                                                                                                                   |
| <b>Watts</b>                        | 85                                                                                                                                                                                    |
| <b>Base Type</b>                    | Medium Screw (E26)                                                                                                                                                                    |
| <b>MOL in/mm</b>                    | 9.96/253                                                                                                                                                                              |
| <b>MOD in/mm</b>                    | 4.02/102                                                                                                                                                                              |
| <b>Mercury Content (mg)</b>         | 4.8                                                                                                                                                                                   |
| <b>HG Form</b>                      | amalgam                                                                                                                                                                               |
| <b>Approx Initial Lumens</b>        | 5700                                                                                                                                                                                  |
| <b>CT deg K</b>                     | 4100                                                                                                                                                                                  |
| <b>CRI</b>                          | >80                                                                                                                                                                                   |
| <b>Rated Life</b>                   | 10,000                                                                                                                                                                                |
| <b>Special Desc</b>                 | Not for use with dimmers, electronic timers, photocells, motion/occupancy sensors, or in totally enclosed fixtures. Use in dry locations only. Use in open socket type fixtures only. |
| <b>Equivalent</b>                   | 350W Incandescent                                                                                                                                                                     |
| <b>Ambient Operating Temp Range</b> | 40° C (104° F) max. Open socket type fixture.                                                                                                                                         |
| <b>Approvals</b>                    | cULus, IMERC, TCLP Compliant                                                                                                                                                          |

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335