

DL60 (PAR38)

focusindustries.com/product/dl60-par38/



CONSTRUCTION: 5.20" dia. X 11.22" Aluminum or Brass Bullet, Angle Cut

LENS: High Impact glass convex lens

LED: 15w PAR38 LED 15° (L156) 3000K, 1350 Lumen

LED OPTION: 15w PAR38 LED 40° (L158) 3000K, 1350 Lumen

LIFETIME RATING: 50,000 hours

SOCKET: High temperature ceramic Medium Base with 250°C silicone lead wires

WIRING: Black 3ft 18/2 zip cord from base of fixture. For 25ft 16/2 fixture lead wire, add (-25F) to part number

CONNECTION: FA0 Quick Connect (not supplied) from fixture to main cable

MOUNTING: FA26BLT/BRS 120v-277v ABS Mounting Pedestal, Cast Cap

FINISH: Aluminum – Black Texture Finish (BLT) (Powder coat options available)

Brass – Unfinishes (Acid & Premium finishes available)

(powder coat and acid finishes over Brass, and Copper are considered custom and non-returnable)

Categories: [Directional](#), [New Products](#)

Catalog No.	Description	Lamp
DL60L156BLT	5.20" dia. X 11.22" Aluminum Bullet, Angle Cut	15w PAR38 15° LED
DL60L158BLT	5.20" dia. X 11.22" Aluminum Bullet, Angle Cut	15w PAR38 40° LED
5.20" dia. X 11.22" Aluminum Bullet, Angle Cut	No Lamp	