



LED SURFACE MOUNT LIGHTS SL-57 SERIES



SPECIFICATIONS

CONSTRUCTION:

SL-57-C: Extruded square aluminum or brass housing with matching canopy

SL-57-J: Extruded square aluminum or brass housing with matching back plate for mounting over single gang junction boxes

LENS: None

LIGHT SOURCE: 12v, 4w 300 lumen or 12v, 2w 150 lumen integrated round LED flat panel, warm white 3000K; optional cool white 5200K available (add -52 after wattage in part number)

LIFETIME RATING: 50,000 hours

12V DRIVER: 4w 350mA output, 12v AC input. Voltage range of 9 to 18 volts with optimum operating range of 10 to 15 volts for consistent performance and brightness. For use with magnetic transformers only.

120V DRIVER: 6w 350mA output, 120-277AC input **SOCKET:** None - LED is hard wired inside fixture

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only) For 25 foot 16/2 fixture lead wire add -25F to catalog number.

120v: Standard black, white, green

MOUNTING: SL-57-C: Mounting plate with hardware and color matching thumb screws

SL-57-J:Two matching screws


FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available

Brass - Unfinished brass. Optional finishes available




ORDERING INFORMATION									
CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT						
SL-57-CLEDP412VBLT	Aluminum Surface Light, canopy, 12v driver	4w LED pane	l 1.0 lbs.						
SL-57-CLEDP212VBLT	Aluminum Surface Light, canopy, 12v driver	2w LED pane	l 1.0 lbs.						
SL-57-CLEDP412VBRS	Brass Surface Light, canopy, 12v driver	4w LED pane	l 2.0 lbs.						
SL-57-CLEDP212VBRS	Brass Surface Light, canopy, 12v driver	2w LED pane	l 2.0 lbs.						
SL-57-JLEDP412VBLT	Aluminum J-box cover Light, 12v driver	4w LED pane	l 1.0 lbs.						
SL-57-JLEDP212VBLT	Aluminum J-box cover Light, 12v driver	2w LED pane	l 1.0 lbs.						
SL-57-JLEDP412VBRS	Brass J-box cover Light, 12v driver	4w LED pane	l 2.0 lbs.						
SL-57-JLEDP212VBRS	Brass J-box cover Light, 12v driver	2w LED pane	l 2.0 lbs.						

Note: For 120v models change "12V" in part number to "120V"







29mm	- 89	lmm -	
	0	0	3.5" 89mm
3.5"			

SL-57-C

INFORMATION	

FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE

LAKE FOREST, CA 92630

JOB INFORMATION	
Туре:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	

-BLT -ATV -BRT -CAM -WTX -HTX -RST -WIR -WBR -STU -RBV -CPR -BAR/CAR -BAV/CAV -BA	I	Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
		-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT

SL-57 Cut Sheet 101515 **BRASS & COPPER ONLY**

(949) 830-1350 • FAX (949) 830-3390

www.focusindustries.com sales@focusindustries.com

LED SURFACE MOUNT LIGHTS SL-57 SERIES

LIGHT DISTRIBUTIONS AND PHOTOMETRICS

