

Ground Fault Products

2 Pole 3 Wire Grounding**Commercial Grade****Straight Blade Automatic and Manual Set Portable GFCI Line Cords**

Meets 2003
UL 943
Requirements

**Circuit Guard®
Portable GFCI Single Outlet**

15A
120V AC



Description	Catalog Numbers
2' (45.7 cm) GFCI line cord, automatic set.	GFP2CA
2' (45.7 cm) GFCI line cord, manual set.	GFP2CM
25' (45.7 cm) GFCI line cord, automatic set.	GFP25CA
25' (45.7 cm) GFCI line cord, manual set.	GFP25CM



GFP2CA

**Circuit Guard®
Portable GFCI Triple Tap Outlet**

15A
120V AC

Description	Catalog Numbers
2' (45.7 cm) GFCI line cord, automatic set.	GFP2TTA
2' (45.7 cm) GFCI line cord, manual set.	GFP2TTM
25' (45.7 cm) GFCI line cord, automatic set.	GFP25TTA
25' (45.7 cm) GFCI line cord, manual set.	GFP25TTM



GFP2TTA

**Circuit Guard®
OEM Equipment Integrated Cord Sets**

15A
120V AC

Description	Catalog Numbers
15' (45.7 cm) GFCI with /flying leads, automatic set.	GFP15LA
15' (45.7 cm) GFCI with /flying leads, manual set.	GFP15LM
35' (45.7 cm) GFCI with /flying leads, automatic set.	GFP35LA
35' (45.7 cm) GFCI with /flying leads, manual set.	GFP35LM



GFP15LA

Specifications**Portable GFCI Line Cords**

Trip Level	4 to 6 mA.
Trip Time	.025 sec. nominal.
Frequency	60 Hz.
Voltage	120V AC +10% - 15%. Incorporates no voltage release feature.
Current	15A.
Maximum Interrupting Capacity	2000A.
Operating Temperature	-35°C to +66°C or -30°F to +150°F.
Maximum Humidity	95%.
Housing	High-impact, UV stabilized PVC. UL 94V-0 flammability classification. Meets UL and CSA watertight requirements.
Cord Type	Adhesive bonded. #14 AWG SJTW-A (UL), SJTW (CSA).
Visual Fault Indication Light On Listing and Standards	Indicates fault. Meets UL943 2003 Class A UL File E41978 CSA Certified.
Code	Meets all NEC & CEC requirements.