


HBLALU3800 and HBLALU4800 Series

Fittings for HBLALU3800 and HBLALU4800 Aluminum Raceway

Couplings (Pair)

To join lengths of HBLALU3800 or HBLALU4800 base.




HBLALU01
A: 2.85" (72.39)
B: 4.00" (101.80)

Aluminum

Grounding Adapter

For connection of equipment grounding.
#10-32 Locking screws included.




HBLALU09
A: 2.35" (59.8)
B: 1.18" (30.0)

Galvanized Steel

Internal Corner Coupling

For butting two raceway sections to form an internal 90° turn in a raceway run.



HBLALU17A
A: 4.00" (101.80)
B: 2.00" (50.83)

Anodized Aluminum

Blank Cover

To cover 12 in. (305.00) section of raceway.




HBLALUBL
A: 3.00" (76.20)
B: 12.00" (304.80)

Anodized Aluminum

Hubbell iSTATION™ Cover

For mounting Hubbell iSTATION™ Modules. For the **HBLALUPB** use the **KPIMBZGY** on page 68 with modules from page 69. For the **HBLALUPBA** use the **IMF1GY** on page 69 or any **IFPxxGY** plates on page 68.



HBLALUPB
A: 3.00" (76.20)
B: 12.00" (304.80)


Anodized Aluminum

HBLALUPBA
A: 3.00" (76.20)
B: 12.00" (304.80)

Anodized Aluminum

Duplex Receptacle Cover

For duplex receptacles and duplex communication plates.



HBLALUDR
A: 3.00" (76.20)
B: 12.00" (304.80)


Anodized Aluminum

HBLALU34DRBM
(Base Mounted Device)
A: 3.00" (76.20)
B: 12.00" (304.80)

Anodized Aluminum

Rectangular Style Line® Cover

For Style Line rectangular duplex receptacle, GFCI, surge device or rectangular communication device.



HBLALUG
A: 3.00" (76.20)
B: 12.00" (304.80)

Anodized Aluminum

HBLALU34GBM
(Base Mounted Device)
A: 3.00" (76.20)
B: 12.00" (304.80)

Anodized Aluminum