












HBLALU4800 Series

Available in
PRE-WIRED



Raceway		Catalog Numbers	Length	Color
Two Channel Base Satin anodized finish. Packed 40 ft. (12.19m) per carton, 10 ft. (3m) lengths. Assembled cover and base dimensions. W: 6.00" (152.40) H: 2.25" (57.15)	 	HBLALU4800B10	10 ft.	Anodized Aluminum
		A: 2.10" (53.34) B: 6.00" (152.40)		
Cover Satin anodized finish. Packed 40 ft. (12.19m) per carton, 5 ft. (1.5m) lengths.	 	HBLALUC5	5 ft.	Anodized Aluminum
		A: 3.00" (76.20)		
Fittings		Catalog Numbers		Color
Wire Clip Used for holding conductors in place on raceway. Can be used for either HBLALU3800 or HBLALU4800 Raceway.	 	HBLALUWC		Anodized Aluminum
		A: 1.00" (25.40)		
Internal Elbow (Two Channel) For making a 90° internal turn in a raceway run.	 	HBLALU4817*		Anodized Aluminum
		A: 6.00" (152.40) B: 6.00" (152.40)		
Inverted Internal Elbow (Two Channel) For connecting a vertical run of HBLALU4800 with a horizontal run with its cover facing up.	 	HBLALU4817N*		Anodized Aluminum
		A: 6.00" (152.40) B: 5.98" (151.89)		
External Elbow (Two Channel) For making a 90° external turn in a raceway run.	 	HBLALU4818*		Anodized Aluminum
		A: 6.00" (152.40) B: 6.00" (152.40)		
Flat Elbow (Two Channel) For making a 90° flat turn in a raceway run.	 	HBLALU4811*		Anodized Aluminum
		A: 9.00" (228.60) B: 9.00" (228.60)		
Tee (Two Channel) For branch connections of two runs of HBLALU4800 Raceway.	 	HBLALU4815*		Anodized Aluminum
		A: 9.00" (228.60) B: 9.00" (228.60)		
Blank End Fitting (Two Channel) For closing end of raceway.	 	HBLALU4810B		Anodized Aluminum
		A: 6.00" (152.40) B: 2.31" (58.74)		
Entrance End Fitting (Two Channel) For feeding raceway, has two concentric 1/2 in. and 3/4 in. trade size KOs.	 	HBLALU4810B2		Anodized Aluminum
		A: 6.00" (152.40) B: 2.31" (58.74)		
Cover Clip To cover seam where lengths of HBLALU4800 Raceway come together.	 	HBLALU4806		Stainless Steel
		A: 1.38" (34.92)		

Note: * HBLALU01 couplings included.