© 2023 Kichler Lighting LLC. All Rights Reserved.

MOTOR FINISH



Oil Brushed Bronze

BLADE FINISHES

Weathered White Walnut, Weathered White Walnut



Dimmable



AR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High

4945

RPM Revolutions Per Minute on High

127

POWER USAGE Watts on High (Excludes Lights)

57

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

87

SPECIFICATIONS

Performance			
CFM (High) Watts (High)	4945 57	RPM (High) Airflow Efficiency CFMW (High)	127 87
Motor Specifications			
Amps (High) Motor Type	0.48 AC Induction	Motor Size Primary Material	153MM X 18MM Steel
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length Low Ceiling Adaptable Connector Mounting Style	7.0 feet 78" No Yes Downrod	Interior/Exterior Location Rating Max Stem Tilt Direct Wire Wire Connectors	INTERIOR Dry 30.0 Degrees Yes Wire Nuts
Dimensions			
Downrod 1 Weight Height	1.00 OD X 4.50" 17.20 LBS 14.50"	Base Backplate Blade Sweep Width	5.75" DIA 60 60.00"
Light Source			
Downlight Included Dimmable Kelvin Temperature Diffuser Description	Yes Yes 3000K Etched Cased Opal	Downlight Option Color Rendering Index Initial Lumens Downward-facing Bulbs	Integrated 80 1600 1 X 17
Photometrics			
Delivered Efficacy (Lumens/Watt)	94		
Electrical			
Input Voltage	120.00V		

FIXTURE ATTRIBUTES

Blade Finish & Specs			
Blade Finish 1 Blade Material Blades Included	Weathered White Walnut Solid Wood Yes	Blade Finish 2 Blade Pitch Number of Blades	Weathered White Walnut 14 3
Included Control			
Wall Control Included Limited/Full Function	Yes Limited	# of speeds	3
Product/Ordering Information			
SKU UPC	300075OBB 783927027151	Finish Style	Oil Brushed Bronze Contemporary
Housing			
Fan Primary Control System	3 Speed Wall Control Limited Function		
Warranty			

www.kichler.com/warranty

Compatible Accessories

CoolTouch™ Transmitter Limited Function White, Dual Threaded 12" Downrod Oil Brushed Bronze

ALSO IN THIS FAMILY



300075BSS 300075AP 300075NBR

You can see all products in this family by searching **Kichler.com**