


#### MOTOR FINISH



#### BLADE FINISHES

Weathered Steel



#### AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
7308	140	32	225

CFM (Low)	2628
RPM (Low)	51
Watts (Low)	3

#### SPECIFICATIONS

##### Light Source

Downlight Included	Yes	Downlight Option	Removable
Downward-facing Bulbs	1 X 17W	Watts (High)	32
Watts (Low)	3	Dimmable	Yes
Dimmable Notes	Recommended for use with Kichler Fan Controls		

##### Photometrics

Color Rendering Index	80	Color Temperature Range	3000
Kelvin Temperature	3000K		

##### Electrical

Amps (High)	0.50	Amps (Low)	0.06
Motor Size	165M	Motor Type	DC

##### Dimensions

Downrod 1	1.00 OD X 6.00"	Base Backplate	6.75 DIA
Weight	28.40 LBS	Height	16.25"
Width	60.00"		

##### Mounting/Installation

Minimum Distance from Fan to Floor	7 feet	Interior/Exterior	Exterior
Lead Wire Length	78"	Location Rating	Wet
Mounting Weight	28.40 LBS		

#### FIXTURE ATTRIBUTES

##### Product/Ordering Information

SKU	300300WSP	Finish	Weathered Steel Powder Coat
Style	Transitional	UPC	783927511810

Housing			
Wall Control Included	Yes	Diffuser Description	Etched Cased Opal
Primary Material	STEEL	Max Stem Tilt	30 Degrees
Blade Finish & Specs			
Blade Finish 1	WEATHERED STEEL	Blade Material	ALUMINUM
Blade Pitch	13	Blade Sweep	60
Blades Included	Yes	Number of Blades	6
Warranty			
<a href="http://www.kichler.com/warranty">www.kichler.com/warranty</a>			

## ALSO IN THIS FAMILY



300300OZ



300300SBK



300301OZ



300301SBK

You can see all products in this family by searching **Kichler.com**